



wirefield

ANGLED WALLPACK

30,000 hrs
L80/B50

ANGLED WALLPACK



Technical Specification

- Surface mounted LED Bulkhead.
- Frosted polycarbonate diffuser
- Opal diffuser to minimise glare.
- IP65.
- IK08.
- Integral emergency available

Features

Wattage	13w to 28w
Lumens per Watt	Up to 28
CRI	80
L**B**	30,000 hours L80 B50
Driver	Fixed Output
Colour Temperature	4000k/3000k
Temperature Rating	-25°C to +40C (excluding emergency)

LIGHTING INNOVATION FOR AMENITY APPLICATIONS



wirefield

ANGLED WALLPACK

Product Specification

Code	Watts	Delivered lumens	L x W x D (mm)	Weight (kg)
AWP1134K	13	1829	319 x 165 x 265	1.85
AWP1184K	18	2535	319 x 165 x 265	1.85
AWP1284K	28	3567	319 x 165 x 265	1.85

Control Options

Driver Options:

Fixed Output/DALI

Emergency Options

Emergency Options:

3hr Integral Maintained

Self Test Emergency

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are CE certified

LIGHTING INNOVATION FOR AMENITY APPLICATIONS

Tel: 0844 847 5100 Fax: 0844 847 5101 Web: www.wirefield.co.uk Email: sales@wirefield.co.uk