

Specifications Table for FTXTP-A

					FTXTP25A5V1B	FTXTP35A5V1B
Power input	Cooling		Nom.	kW	0.032	0.032
	Heating		Nom.	kW	0.032	0.032
Casing	Colour				White	White
Dimensions	Unit		Height	mm	286	286
			Width	mm	770	770
			Depth	mm	225	225
Weight	Unit			kg	9	9
Fan	Air flow rate	Cooling	High	m³/min	11	11
			Medium	m³/min	7.9	7.9
			Low	m³/min	5	5
			Silent operation	m³/min	3.7	3.7
		Heating	High	m³/min	10.5	10.5
			Medium	m³/min	9	9
			Low	m³/min	5.5	5.5

			Silent operation	m ³ /min	4.4	4.4
Sound power level	Cooling			dBA	58	58
	Heating			dBA	58	58
Sound pressure level	Cooling	High	dBA	43	43	
		Medium	dBA	35	35	
		Low	dBA	26	26	
		Silent operation	dBA	21	21	
	Heating	High	dBA	43	43	
		Medium	dBA	35	35	
		Low	dBA	26	26	
		Silent operation	dBA	21	21	
Refrigerant	GWP				675	675
Piping connections	Liquid	OD	mm	6.35	6.35	
	Gas	OD	mm	9.5	9.5	
	Drain				18	18
Control systems	Infrared remote control				ARC480A78	ARC480A78
Standard Accessories	FTXTP25A5V1B				1	
	Installation manual				1	1
	Wireless remote control				1	1

	Screw cover		2	2
	AAA dry-cell batteries		2	2
	General safety precautions		1	1
	Operation manual		1	1
	Titanium apatite deodorizing filter		1	1
	Silver particle filter		1	1
	Remote control holder		1	1
	Screw bag		1	1
Power supply	Name		V1	V1
	Phase		1~	1~
	Power supply=-Frequency	Frequency	50	50
	Power supply=-Voltage	Voltage	220-240	220-240
Notes			(1) - Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m	(1) - Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m
			(2) - Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent	(2) - Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent

		refrigerant piping: 5m	refrigerant piping: 5m
		(3) - See separate drawing for electrical data	(3) - See separate drawing for electrical data
Standard Accessories	FTXTP35A5V1B		1

