



wirefield PROLED50 NGBF

50,000 hrs
L80/B50

DECORATIVE BOLLARD



Technical Specification

- Extruded Aluminium Body.
- Flange Mounting Plate Included.
- Clear Polycarbonate Diffuser.
- IP65.
- IK08.
- RAL colour options.


Features

Wattage	14w
Lumens per Watt	Up to 114
CRI	80 +
L**B**	50,000 hours L80 B50
Driver	Fixed Output / Dali / Switch Dim
Colour Temperature	4000k
Temperature Rating	-30°C to +35°C

LIGHTING INNOVATION FOR ARCHITECTURAL APPLICATIONS

Product Specification

Code	Watts	Delivered lumens	CCT	Ø x H (mm)	Weight (kg)
NGBF1143K	14	1542	3000K	165 x 805	3.5
NGBF1144K	14	1627	4000K	165 x 805	3.5



Control Options

Driver Options:

Fixed Output

DALI Driver

Switch Dim

LED Options

Additional Options:

CCT 3000K

Accessories

Optional Accessories:

RAL colour options

Full photometry and LDT files available on request

Designed & manufactured to comply with EN 60598 and are UKCA & CE certified

LIGHTING INNOVATION FOR ARCHITECTURAL APPLICATIONS