

Phase 1 – Pallet Racking

Racking Reference – PO1 – 6 Bays – Crossed bays at reduced height



PO1 – Full Height:

Bay Type	P01	
Frame Height (mm)	4000	
Frame Depth (mm)	900	
Beam Length (mm)	2700	
Number of Levels	3	
Beam Level 1 (mm)	1000	
Beam Level 2 (mm)	2000	
Beam Level 3 (mm)	3000	
Max. UDL per Level (kgs)	2000	
Max. Bay Load (kgs)	6000	

PO1 – Reduced Height:

Bay Type	P01	
Frame Height (mm)	3200	
Frame Depth (mm)	900	
Beam Length (mm)	2700	
Number of Levels	3	
Beam Level 1 (mm)	1000	
Beam Level 2 (mm)	2000	
Beam Level 3 (mm)	3000	
Max. UDL per Level (kgs)	2000	
Max. Bay Load (kgs)	6000	

Racking Reference – PO2 – 5 Bays – Crossed bays at reduced height



PO2 – Full Height:

Bay Type	P02	
Frame Height (mm)	4500	
Frame Depth (mm)	900	
Beam Length (mm)	2700	
Number of Levels	3	
Beam Level 1 (mm)	1000	
Beam Level 2 (mm)	2000	
Beam Level 3 (mm)	3000	
Max. UDL per Level (kgs)	2000	
Max. Bay Load (kgs)	6000	

PO2 – Reduced Height:

Bay Type	P02	
Frame Height (mm)	4000	
Frame Depth (mm)	900	
Beam Length (mm)	2700	
Number of Levels	3	
Beam Level 1 (mm)	1000	
Beam Level 2 (mm)	2000	
Beam Level 3 (mm)	3000	
Max. UDL per Level (kgs)	2000	
Max. Bay Load (kgs)	6000	