

Technical specification	
Size of Tile	420mm x 330mm
Minimum Pitch	22.5° Smooth (75mm headlap) 17.5° Smooth (100mm headlap)
Maximum Pitch	90°
Minimum Headlap	75mm (22.5° and above) 100mm (below 22.5°)
Maximum Gauge	345mm
Cover Width	295mm (nominal)
Covering Capacity	9.7 slates/m ² at 75mm headlap 10.5 slates/m ² at 100mm headlap
Weight of Tiling	44kg/m ² (0.43kN/m ²) at 75mm headlap 47.5kg/m ² (0.47kN/m ²) at 100mm headlap
Battens Required	2.9 lin.m/m ² at 75mm headlap 3.1 lin.m/m ² at 100mm headlap
Batten Size Recommended	38 x 25mm for rafters/supports not exceeding 1.5m 50 x 25mm for rafters/supports not exceeding 2.5m
Tile Nails	45mm x 3.35mm
Hanging length	395mm (nominal)
Fixing clips	Eaves, verge and slate clips
Authority	BS EN 490

Advantages of using Marley's Edgemere concrete roof tiles:

With its leading edge of only 18mm, the Edgemere has been precision-engineered to be 40% thinner than standard concrete interlocking tiles.

Its large format coupled with a broken-bond laying technique make it ideal for quick and easy installation, saving you time and money, and it is versatile enough to be used on pitches as low as 17.5°.

The Edgemere slate has been designed to integrate seamlessly with Marley's dry fix and ventilation systems into a full holistic roof system, ensuring complete protection from the elements and full compliance with BS 5534.

The product is BES 6001 accredited and can achieve extra credits under BREEAM and HQM. As a roof covering, these tiles have a very low carbon footprint and environmental impact and can score an A+ rating in the BRE Green Guide.