



FFA-A9 / RZAG-A

B-32 BLUEVOLUTION

Indoor Units		FFA35A9	FFA50A9	FFA60A9
Capacity	UK Total Cooling kW	3.32	4.62	5.72
	UK Sensible Cooling kW	2.28	3.40	4.20
	Nominal Cooling kW	3.4	5.0	5.7
	Nominal Heating kW	4.2	5.8	7.0
Seasonal Efficiency (EN14825)	Energy Label Pdesign kW	A++ 3.4	A++ 5.0	A+ 5.7
COOLING	SEER	6.40	6.30	5.80
Seasonal Efficiency (EN14825)	Energy Label Pdesign kW	A 3.10	A+ 3.84	A+ 3.96
HEATING	SCOP	3.80	4.01	4.04
Nominal Efficiency Air Flow Rate (Cooling)	EER/COP High / Nom / Low m ³ /sec	4.00 / 3.71 0.166/0.141/0.108	3.40 / 3.10 0.200/0.166/0.125	3.23 / 2.90 0.241/0.208/0.158
Dimensions (with Decoration Panel)	Height mm	260 (306)	260 (306)	260 (306)
	Width mm	575 (620)	575 (620)	575 (620)
	Depth mm	575 (620)	575 (620)	575 (620)
Weight (with Decoration Panel)	kg	16 (18.8)	17.5 (20.2)	17.5 (20.2)
Sound Pressure (Cooling)	High / Nom / Low dBA	34/30.5/25	39/34/27	43/40/32
Sound Pressure (Heating)	High / Nom / Low dBA	34/30.5/25	39/34/27	43/40/32
Sound Power (Cooling)	dBA	51	56	60

Outdoor Units		RZAG35A	RZAG50A	RZAG60A
Dimensions	Height x Width x Depth mm	820 x 1050 x 480	820 x 1050 x 480	820 x 1050 x 480
Weight	kg	52	52	52
Electrical Details	Power Supply Maximum Input Current (MCA) A	1ph 14.43	1ph 14.63	1ph 16.70
	Max Fuse Size A	16	16	20
Interconnection Wiring	Core / Cable Size Inches (mm)	3+E / 1.5 1/4 (6.4) / 3/8 (9.5)	3+E / 1.5 1/4 (6.4) / 1/2 (12.7)	3+E / 1.5 1/4 (6.4) / 1/2 (12.7)
Pipework	Liquid / Gas Maximum Length m	50	50	50
	Maximum Vertical Rise m	30	30	30
	Precharged to g/m	30	30	30
	Additional charge kg	20	20	20
	Holding charge kg	1.55	1.55	1.55
Sound Pressure (Cooling)	Nominal dBA	48	49	50
Sound Pressure (Heating)	Nominal dBA	48	49	50
Sound Power (Cooling)	dBa	62	63	64
Operating Range (Cooling)	Min / Max °CDB	-20 / +52	-20 / +52	-20 / +52
Operating Range (Heating)	Min / Max °CWB	-20 / +24	-20 / +24	-20 / +24
Air Flow Rate (Cooling)	Nominal m ³ /sec	0.918	0.918	0.918

ECA Eligible

Accessory Ref	Description	Accessory Ref	Description
BRFO60CW	Fully Flat Cassette Decoration Panel - White (Included as standard)	K.CGM	Condensing unit guard size 42-71
BRC1E3A	Premium wired remote controller (Included as standard)	K.CG5	Condensing unit guard size 20-35
BRP069A81	Wifi adaptor for connection to on-line controller	K.CWB90-2	Condensing unit bracket - up to size 71, max weight 90kg of ODU
BRC1H519W	New - wired touch screen remote controller - White	K.DT1	Condensate drip tray for use with K.CWB90-2
BRC1H519S	New - wired touch screen remote controller - Silver	K.R55	Wireless room mounted temperature sensor and receiver
BRC1H519K	New - wired touch screen remote controller - Black	KLIC-DI	KNX Interface for Sky Air and VRV systems
BDBHQ4AC60	Sealing member for decoration panel FFA, FYZQ	KRCS01-4	Remote room mounted temperature sensor
BRC7FB30W	Wireless remote for fully flat cassette Old style decoration panel	KRP1B57 and UK.FB2	Adaptor PCB for interlock to fresh air fan
BRC7F530S	Wireless remote controller for Silver ceiling decoration panel	KRP4A53 and UK.FB2	Unit/group adaptor PCB for remote on/off, status indication and temperature setting
BRC7F530W	Wireless remote controller for White ceiling decoration panel	RS-SE	Service and configuration tool for K.R55
BRFO60AS	Integral PIR sensor for fully flat cassette Silver decoration panel	RTD-10 and UK.FB2	Enhanced function PCB for Sky Air and VRV Duty rotation,
BRFO60AW	Enables energy saving functions	RTD-20 and UK.FB2	Lead Lag control and heating interlock
BRFO60B3	Enables energy saving functions	Energy control PCB for Sky Air and VRV	
BRFO60C5	Integral PIR sensor for fully flat cassette White decoration panel	Modbus interface PCB for Sky Air and VRV	
	Fully Flat Cassette Decoration Panel - Silver		

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



FSC

Daikin Europe NV, participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com

Daikin Airconditioning UK Limited The Heights Brooklands Weybridge Surrey KT13 0NY Tel 0845 6419000 Fax 0845 6419009 daikin.co.uk