

Materials Schedule – End of Life Services – 194-196 Dunsbury Way - May 2020.

As per the requirements as set in condition 4 of planning application APP/20/00262 – I am pleased to enclose the full specification of materials to be used externally on the building to the Local Planning Authority for their approval.

Shop Front

Standard powered coated aluminium shop front and manual door with a 1000mm opening

Material specification

100 x 45mm sections
Double glazed toughened clear glass
140mm formed cill detail
Power coated in RAL7015 Matt

Front Side Door

Senator steel door and frame set with a 2400mm opening

Material specification

Door

46 mm overall thickness.
Made up of 3 mm plate external skin with 16 gauge internal skin.
The Primary leaf to have additional 3mm stiffener plate to give a 6mm astragal with the secondary leaf have a 20mm x 20mm anti-crowbar strip to sit against the astragal.
Primed for painting on a mild steel profiled pan with centre supports infilled with Rockwool insulation.

Frame

3 mm press formed single rebate mild steel with 5 no. fixings to each side.
Fixings to be 12mm dia x 100mm /125mm long bolt head expanding masonry type

Finish 2 coats zinc phosphate primer 2 coats gloss 7015

Fence

Close Boarded, soft wood, pressure treated timber fence panels with either concrete or timber posts.