


Rivendale

Colour: Blue-Black



Request a sample

Benefits and Sizes

Blue-Black	600mm x 300mm
Cromleigh Graphite	600mm x 300mm

Technical data

Fixing method	Nail and rivet	Slate hooks
Size of slate	600mm x 300mm	600mm x 300mm
Minimum pitch**: Moderate exposure	22.5° (100mm lap) 20° (110mm lap)	20° (150mm lap)
Minimum pitch**: Severe exposure	25° (100mm lap) 22.5° (110mm lap)	20° (150mm lap)
Maximum pitch	90°	90°
Typical laps	100, 110mm	150mm
Maximum gauge	245 - 250mm	225mm
Slate thickness	4mm	4mm
Covering capacity (net)	13.4 slates/m ² at 100mm lap 13.6 slates/m ² at 110mm lap	14.8 slates/m ² at 150mm lap
Weight of slating (approx)	20.4 kg/m ² (0.20 kN/m ²) at 100mm lap 20.9 kg/m ² (0.20 kN/m ²) at 110mm lap	22.8 kg/m ² (0.21 kN/m ²) at 150mm lap
Battens required (net)	4.00 lin.m/m ² at 100mm lap 4.08 lin.m/m ² at 110mm lap	4.45 lin.m/m ² at 150mm lap
Batten size	38 x 25mm for rafters/supports not exceeding recommended 450mm centres	38 x 25mm for rafters/supports not exceeding recommended 450mm centres
(fixed to BS 5534)	50 x 25mm for rafters/supports not exceeding 600mm centres	50 x 25mm for rafters/supports not exceeding 600mm centres
Fixings	Slate nails (30 x 2.65mm) Copper disc rivets (19mm dia. x 2mm stem)	Slate nails*** (30 x 2.65mm) Copper disc rivets*** (19mm dia. x 2mm stem)
Fitting Screws	14 gauge self sealing	14 gauge self sealing
Authority	BS EN 492	BS EN 492

Cedral fibre cement slates meet the strength requirement of BS EN 492, achieving an average

bending movement greater than 50 NM/M (Class B). Cedral Fibre Cement Slates have an average density of 1970kg/m³ (minimum of 1750kg/m³) when tested to BS EN492 and a nominal thickness of 4mm.

*Made to order

**The minimum recommended pitch and lap may be influenced by special circumstances, please contact the Technical Advisory Team

***For local areas of roof

Related projects



Rivendale

Blue-Black

More

Follow us on:



Our info

Etex (Exteriors) UK Ltd
Wellington Road
Burton upon Trent
Staffordshire
DE14 2AP

VAT: GB 860228536

Get in touch with us

+44 01283 501 555

Ask us a question

Technical enquiry

Etex Group
All rights reserved
[Cookie Policy](#)
[Privacy Policy](#)
[Terms and Conditions](#)

etex inspiring ways
of living