WHY TREE PROTECTION IS NEEDED

1) Soil compaction kills roots– caused by plant movement and storage of materials within protected areas.

2) Changing the ground level around trees kills roots within the top 600mm of soil. Even the removal of the top 200mm can cause damage.

3) Soil pollution kills roots– Dumping fuel/drainage or cement washings can contaminate the soil and kill or limit roots.

4) Raising & lowering levels kills roots– no soil used to increase, reduce or level ground around trees. Roots can't live in, or tolerate, soil compacted with heavy plant causing damage to the tree.

5) Bark and branch damage– bark removed and branch damage can allow disease and fungi into the trees.

The impact of any of the above can take years to show– trees can have huge reserves of food and water.

LEGEND

TREE PROTECTION FENCING & CONSTRUCTION EXCLUSION ZONE

All fencing must be installed prior to any plant activity or site establishment, including demolition, soil stripping, material storage, and welfare facilities.

Once erected, all TPF will be regarded as sacrosanct, and will not be moved or altered without written permission by the project arboricultural consultant and any associated local planning authority. The TPF is suitable in cases of high security requirement, and will comprise a 2.4m high fence of Heras type panels, mounted on scaffold poles driven into the ground. Alternatively, and as per BS5837, the fencing may be of a design to suit the individual circumstances, but must be approved by the project arboricultural consultant and the relevant local planning authority and retained for the duration of the construction period. Where the TPF is to be moved temporarily to allow for construction to take place, the project arboricultural consultant must be informed in advance. All moves must be recorded on the drawing.

Standard scaffold fencing

Heras gauge 2.4m high mesh fencing on scaffold feet (if required)

Fencing secured to uprights and cross-members with wire ties

Ground level

Uprights driven into the ground to a minimum depth of 0.6m

Standard scaffold clamps

A. DEMOLITION PROTOCOL SPECIFICATION

Before any work starts on site, the contractor must familiarise with the precautions and appropriate line of demarcation to protect the RPA of retained trees close to / accessible from the demolition area.

BUILDING WORKS IN THE RPA

TREES TO BE REMOVED

A CATEGORY TREE
B CATEGORY TREE
C CATEGORY TREE
U CATEGORY TREE

ROOT PROTECTION AREA (RPA) FOR RETAINABLE TREES

SUPPORTED EXCAVATION

RESTRICTIONS WITHIN TREE PROTECTION AREAS

Within the notional zones of the fencing, the following shall apply:

- No mixing of cement or use of other materials or substances shall take place within a root protection area or close enough to it that seepage or displacement could cause them to enter a root protection area.
- No alteration to or any other works whatsoever shall be carried out to the trees other than in accordance with the approved proposals without the prior written approval of the retained arboriculturist.
- No roots shall be severed or damaged during any development works unless agreed by the retained arboriculturist.
- No storage of plant or materials.
- No parking of vehicles or placing of temporary buildings or welfare facilities.
- No fires shall be lit.
- No dumping of waste.

In addition to the above, the following requirements are expressly applicable to trees:

- Any excavation within the root protection area (or adjacent to it where it could encroach within the root protection area) must be carried out carefully and by hand, avoiding damage to roots 25mm or more in diameter unless otherwise agreed in writing by the retained arboriculturist.
- No fire should be lit such that flames come within four metres of any tree.

NOTE:
FOR PLANNING PURPOSES ONLY
DO NOT SCALE FROM DRAWING

Rev	Date	Details	Drawn
G	20.02.2018	s278 added & T3 &4, T13 & T14 shown removed	MW
F	07.02.2018	Revised layout	MW
E	29.11.2017	Revised layout	MW
D	23.11.2017	Extension on 142 added	MW
C	16.11.2017	s278 Trees and layout added	MW
B	18.10.2017	Revised by ext	MW
A	22.02.2017	Revised layout	MW

ACD ENVIRONMENTAL

HEAD OFFICE
Radbourne Rd Business Centre, Grange Lane, Mannebury, SN10 2ES
Tel: 01666 825646

Courtyard House, Mill Lane, Godalming, GU7 1EY
Tel: 01483 425714

Suite 6, Crescent House, Yonge Close, Eastleigh, SO50 9QJ
Tel: 02382 026300

9 Brownlow Road, Cambridge, CB4 3NG
Tel: 07825 868654

email: mail@acdenv.co.uk
www.acdenvironmental.co.uk

Copyright of ACD. All rights asserted in Chapter IV of the Copyright, Designed and Patents Act 1988 (Moral Rights). Reproduction of this plan is not to be done without ACD and all fees have been paid in full.

BARRATT LONDON

scheme: Havant Road
Emsworth, Hampshire
client: Barratt Homes
drawing: Tree Protection Plan
date: July 2016
scale: 1:500@A0
dwg no: BDWS20345-03G
drawn: MW checked: TRG