

Description – Cotswold 20mm

Shape - Angular

Aggregate Type – Dolomitic Limestone

Colour- Buff



Grading

Sieve Size	Typical Grading	Specification Limits
40mm	100%	100
31.5mm	100%	98-100
20mm	89%	80-99
14mm	41%	20-70
10mm	8%	0-20
4mm	2%	0-5
0.063mm	1.4%	0-4

Specific Product Data

Ph Value	7.9
Loss on Ignition @ 1000C	46.9%
CO ₂ – Calcium Dioxide	
CaCO ₃ - Calcium	
Carbonate Equivalent	

Sample Basis		%
Al ₂ O ₃	Aluminium Dioxide	0.4
CaO	Calcium Oxide	29.36
CaCO ₃	Calcium Carbonate	
Fe ₂ O ₃	Iron Oxide	0.35
MgO	Magnesium Oxide	21.7
MgCO ₃	Magnesium carbonate	
MnO	Manganese Oxide	0.1
P ₂ O ₅	Phosphorous Peroxide	0.01
K ₂ O	Potassium Oxide	0.14
SiO ₂	Silica	0.84
Na ₂ O	Sodium Oxide	0.1
SO ₃	Sulphur Trioxide	0.02
TiO ₂	Titanium Dioxide	0.02
BaO	Barium Oxide	0.01