

36-38 North Street Emsworth Materials

Windows

Hidden Spring Box Sash Windows in white

Timber Species Engineered Redwood, Engineered Meranti Profiles Traditional ovolo mouldings

Colour OLIVE GREEN

Glazing squares – 18mm,

Dummy transoms – 72mm,

Glass 24mm (4/16/4) double glazed units as standard with soft-coat, energy saving glass and argon gas filled sealed units.

Brick

Wienerberger Pagus Grey/Black Front elevation only

Dimensions: 215x102.5x65mm

Size tolerances, mean and range T1 / R1

Durability F2

Active soluble salts to EN 771-1 S2

Minimum compressive strength ; 12 N/mm²

Maximum Water Absorption = 19 %

Wienerberger Warnham Red Stock - side and rear elevations

Size tolerances, mean and range T2 / R1

Durability F2

Active soluble salts to EN 771-1 S2

Minimum compressive strength ; 12 N/mm²

Maximum Water Absorption = 15 %

Roof Tile

Marley Eternit Plain - colour Dark Red

Size of Tile

267mm x 168mm

Minimum Pitch 35°

Maximum Pitch 90°

Minimum Headlap 65mm (roof)

Maximum Gauge

100mm (roof)

Cover Width 168mm

Covering Capacity

60 tiles/m² at 100mm gauge (roof)

Weight of Tiling

73.8kg/m² (0.72 kN/m²) at 100mm gauge (roof)

Battens Required

73.8kg/m² (0.72 kN/m²) at 100mm gauge (roof)

Batten Size Recommended

38 x 25mm for rafters/supports not exceeding 600mm centres

Tile Nails 38mm x 2.65mm