

# Civik / technical data sheet

Civik staircases are characterized by a landing which allows the staircases to be fitted to openings of any shape or size.

Civik has an adjustable height of between 252 and 305 cm.

## STEEL COLOURS

GREY,  
WHITE OR BLACK



Table 1


|          |                        | SUPPLEMENTARY ITEMS |                                                                      |       |           |
|----------|------------------------|---------------------|----------------------------------------------------------------------|-------|-----------|
|          | STAIRCASE HEIGHT IN CM | RISES               | TREADS                                                               | POLES | HANDRAILS |
| INCREASE | from 336 to 376        | 16                  | + 3                                                                  | + 1   | + 1       |
|          | from 315 to 352        | 15                  | + 2                                                                  | + 2*  | + 1       |
|          | from 294 to 329        | 14                  | + 1                                                                  | -     | -         |
| STANDARD | from 273 to 305        | 13                  | 12 TREADS + 1 UNIVERSAL LANDING<br>+ RAILING WITH VERTICAL BALUSTERS |       |           |
| DECREASE | from 252 to 282        | 12                  | -                                                                    | -     | -         |
|          | from 231 to 258        | 11                  | -                                                                    | + 1*  | -         |
|          | from 210 to 235        | 10                  | -                                                                    | + 1*  | -         |




RISE ADJUSTABLE FROM 21 TO 23.5 CM

\* REPLACES THE EXISTING 125 CM POLE IN THE CIVIK STAIRCASE


## Ø 120 cm



## Ø 140 cm



## Ø 160 cm



## DIAMETERS

The diameters of the staircase are 120, 140 and 160 cm. The recommended opening in the floor is at least 5 cm larger than the diameter of the staircase. Example: Ø staircase 120 cm = Ø opening 125 cm.

