

Kitemark™ Certificate

This is to certify that:

Munster Joinery Ltd
Ballydesmond
Mallow
Cork
Ireland

Holds Certificate Number:


KM 597797

In respect of:

BS 7412 / PAS 24
Enhanced Security PVCU Doors Fabricator

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.



For and on behalf of BSI:

Gary Fenton, Global Product Certification Director

First Issued: 21/05/2013

Latest Issue: 23/01/2017



Page: 1 of 4

...making excellence a habit.™

Kitemark™ Certificate

No. KM 597797

BS 7412:2007 / PAS 24:2012 - General and enhanced security performance requirements for door assemblies.

This Certificate covers the following residential door system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

PVC-U Single and Double Leaf Residential doorsets

Fabricated and installed in accordance with the latest issue of the following Munster Joinery controlled manual(s):

PVC-U Residential Door System Fabrication and Enhanced Security Manual

System description

The door assemblies are open in or open out*, glaze in only, with compliant IGU (s), laminated on one pane, or approved panelled infills(s), with or without midrails, with welded standard threshold and of otherwise fully welded construction with letterplate* (*dependant on door type). Doors are classified as DKT.

Hardware Options

Paddock PLSP lock and Paddock lift off hinge

Size Limitations and Performance Characteristics

Door Type	Length (mm) - Maximum	Height (mm) - Maximum (including sill)	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009 (except *)
Overall dimensions for doors with approved outer frame and sash profiles:						
Single leaf doors	940	2100	4	5A	5	2000*
Single leaf doors with sidelight	930 800	2010 2010	4	7A	A3	1200
Double leaf doors Open in	1800	2100	4	8A	A3	1200*
Double leaf doors Open out	1800	2100	4	E1000	A3	1200*

* Exposure category as given in Table 1 of PAS 23-1:1999

First Issued: 21/05/2013

Latest Issue: 23/01/2017

Page: 2 of 4

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

Kitemark™ Certificate

No. KM 597797

BS 7412:2007 / PAS 24:2012 - General and enhanced security performance requirements for door assemblies.

This Certificate covers the following residential door system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

PVC-U Passiv Single Leaf Residential doorsets

Fabricated and installed in accordance with the latest issue of the following Munster Joinery controlled manual(s):

PVC-U Passiv Door System Fabrication and Enhanced Security Manual

System description

The door assemblies are open in and glaze in only, with compliant IGU (s), laminated on one pane, or approved panelled infills(s), with midrails and mechanically fixed low threshold and of otherwise fully welded construction with letterplate. Doors are classified as DKT.

Hardware Options

Lock	Hinge
Paddock PLSP	Paddock Lift off hinge

Size Limitations and Performance Characteristics

Door Type	Length (mm) - Maximum	Height (mm) - Maximum (including sill)	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Overall dimensions for doors with approved outer frame and sash profiles:						
Single leaf doors	1000	2100	4	8A	A3	1200

First Issued: 21/05/2013

Latest Issue: 23/01/2017

Page: 3 of 4

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

Kitemark™ Certificate

No. KM 597797

BS 7412:2007 / PAS 24:2012 - General and enhanced security performance requirements for door assemblies.

This Certificate covers the following residential door system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

PVC-U Passiv Double Leaf Residential doorsets

Fabricated and installed in accordance with the latest issue of the following Munster Joinery controlled manual(s):

PVC-U Passiv Door System Fabrication and Enhanced Security Manual

System description

The door assemblies are open in or open out, glaze in only, with compliant IGU (s), laminated on one pane, or approved panelled infills(s), without midrails and with mechanically fixed low threshold and of otherwise fully welded construction. Doors are classified as DKT.

Hardware Options

Lock
Paddock PLSP

Hinge
Paddock Lift off hinge

Size Limitations and Performance Characteristics

Door Type	Length (mm) - Maximum	Height (mm) - Maximum (including sill)	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Overall dimensions for doors with approved outer frame and sash profiles:						
Double leaf doors Open In	1800	2100	4	8A	A3	1200
Double leaf doors Open Out	1800	2100	4	9A	A3	1200

First Issued: 21/05/2013

Latest Issue: 23/01/2017

Page: 4 of 4

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.