

Specification:
 CE Approved BS/EN 12453

Dimensions:
 250mm x 225mm extruded Aluminium beam
 Infill – 30mm diameter x 6mm Wall thickness

Power Requirement:
 230v, Single Phase, 50Hz, 10 Amps

Drive Motor:
 0.75KW's - 1.1KW's, 3 Phase

Maximum Span:
 10 Metres Drive-Through
 (14.5 Metres overall) Single Leaf

Maximum Height
 2.4 Metres (maximum width 10.0 metres)
 3.0 Metres (maximum width 6.0 metres)

Duty Cycle:
 100%

Operation Time:
 4 Seconds per metre (Variable)

Finish:
Steel Components:

- Shot Blasted
- Zinc Phosphate immersion coated
- Zinc Primer
- 2K PU Finish

Aluminium Components:

- Abraded
- 2K PU Finish



The PF9000A Automatic Sliding Gate

The PF9000 Automatic Cantilever Gate unique to our brand the PF9000 is a pioneering concept using a simple yet reliable design it uses an external friction drive mechanism.

Note:

Height: to match existing fence
Width: To match existing aperture

UNIT 2 ASTON ROAD WATERLOOVILLE	AUTOMATIC GATE PROPOSAL	SENTRY SELF STORAGE / 02380 442600
DECEMBER 2016	AL SHEPPARD	AL.SHEPPARD@SENTRYSS.CO.UK