



AFFRESOL LTD
Unit 2 Queensway
Swansea West Business Park
Swansea
SA5 4DJ
Tel. 01792 581197

Bin Store Specification & Requirements

Customer:

Guinness Partnership - Havant

Date: 22/11/2016

Description
<u>Unit Size:</u> Site Specific <u>Panel Height:</u> 1981mm <u>Walls:</u> 70/25mm thick TPR Synthetic Concrete Walling System - Colour TBC and site specific <u>Roof:</u> Plastisol box profile metal sheeting with central daylight panel. Constructed onto a pressure treated timber. Externally finished with facias and flashings. Colour TBC <u>Door:</u> 1880-1885mm x 1981mm Galvanised Double Door Set with multi point locking with inactive leaf fixed with flush bolts. Low profile threshold for ease of access. Colour TBC and site specific. # Prices fixed for 90 days. # Prices exclude VAT. # Installation duration varies site by site. Installation will generally be 3-5 days. # No internal electrics supplied. By others along with connection to the mains. If electrics are a consideration please make allowances for ducting cable up through the base. # Concrete base by others. Must be a minimum of 100mm depth with a 50mm perimeter larger than the external dimensions of the unit. The base must be a smooth trowelled finish and not tamped. Also level as our product has +/-10mm tolerance to unequal bases. NOTE - THE BASE MUST BE LEVEL WITH NEIGHBOURING SURFACE TO ALLOW EASE OF ACCESS FOR THE BINS! Also note if the neighbouring surface is higher than the new concrete base, we would recommend an aco type drain along the front of the unit to prevent water ingress via the door. # Additional charges will be incurred if there are issues with the concrete base. # Prices based on installation & delivery to the specific sites. Prices may alter for additional sites in different locations. # Rainwater goods by others. # Prices subject to second survey to confirm all details. # Payment required within 14 days of delivery.