



NOTES

Soil Landscaping:

- All plants, workmanship and materials to comply with relevant British Standards and Codes of Practice.
- Landscaping operations shall be in accordance with BS 4428 and any imported soil shall be to BS 3582.
- The ground surface and shrubs to be retained should be protected during construction. All trees to be protected by a temporary fence. The fence should be positioned and retained at a distance from the trunk equal to the spread of the crown of the tree and at least 2.4m high. Tree protection fencing to be in line with BS 5637 'Trees in relation to construction'.
- Planting borders to be prepared before planting, incorporating organic chicken pellet fertiliser.
- A minimum thick layer of mulch should be spread over all planting borders to retain moisture and reduce competition from weeds. This will help to encourage rapid plant establishment.
- Topsoil should be provided to the following minimum depths: Grass - 150mm, Shrubs - 300mm, Trees - 750mm x 600mm deep tree pits backed with compost enriched topsoil.
- Trees should be secured against wind stakes and staked and staked and staked when planted. All trees should be planted with a suitable irrigation tube to ensure water is directed straight to the root of the tree.
- Tree-planting close to existing or new walls, fences and hard paved surfaces shall include root directors or proprietary planting tubes to facilitate sound growth and development and avoid root disturbance or damage to walls or paving.
- Tree plantings to be checked on site against final alignment of drains and utility services and adjusted if required.

Maintenance:

- All planting borders and lawned / lawn areas to have a regular water regime programme until they have established, especially during periods of dry weather.
- Initial maintenance of planting should be carried out during fortnightly maintenance visits for the first six months after landscaping and then as required until fully established.
- The areas beneath all landscaping areas should be kept weed free until the plants have established.
- Once plants have established, regular attention to the planting borders will still be necessary to ensure plants are maintained in a healthy state. This should include a trim to shape and top up of much every year in the autumn or spring.
- Light pruning of shrubs, to retain their shape should be carried out after flowering. Severe pruning should only be carried out during the winter months. Dead, diseased or damaged stems should be removed immediately.
- Regular monitoring of tree canopies and foliage is necessary to ensure that damage does not occur to the tree. Any dead or diseased branches should be replaced immediately.
- All existing mature trees should be checked every five years to five years for signs of decay and broken limbs due to storm damage and disease.
- All new plants which die or fail to establish within 5 years of planting shall be replaced with plants of the same species

J	Footprint of house reduced	mw	15.09.16	
H	Storm drainage revised	mw	15.12.15	
G	Site levels indicated	mw	14.12.15	
F	Garage repositioned & roof orientation revised	mw	30.10.15	
E	Drive revised, planting revised	mw	06.10.15	
D	Plan updated	mw	03.09.15	
C	Plan revised	mw	14.08.15	
B	House rotated	mw	04.08.15	
A	Layout revised	mw	30.07.15	
-	Original Issue			
Rev		Down / Date		Chk / Date
This drawing is copyright and must not be disclosed to third parties without permission Scaled dimensions are not to be used for construction				

4 Queensgate
Queens Road
Fareham
Hampshire
PO16 0NW

Tel: 01329 288911
Fax: 01329 221913
E-mail: admin@m2architecture.com

PROJECT

Proposed New Dwelling
7 North Close
Havant

CLIENT

S Bailey & F Askew

DRAWING TITLE

Site Plan

PROJECT NO.	DRAWING NO.	REV.	SCALE
15012	402	J	1:200

m2
architecture
architectural technologists

HAVANT BOROUGH
COUNCIL
23 SEP 2016
RECEIVED