

BANK-FL MIDI



URBAN AND FLOOD

Features:

- Wall mounting
- IP65 (dust tight & water jet proof)
- IK08 (5 joules) shock resistance
- Energy efficient Osram LEDs
- Available in 5700K (daylight)
- CRI 80
- Zero upward light
- Average 50,000 hrs - L70 B10

Options:

- Dimming versions available
- 3000K (warm white) or 4000K (cool white) available - on special request
- Technical lighting controls (please consult our technical department)



Material:

- Body: aluminium
- Lens: polycarbonate

Finish:

- Body: powder coated
- Lens: clear


Colour:

- 01 White
- 02 Black
- 04 Grey


Beam Angles:



Technical



Photometrics



Bank-FL Midi						Ordering Code
Wattage	Colour Temperature	Delivered Lumens	Luminous Efficacy	Weight (Kg)	Windage (m²)	
7W LED	5700K	1420lm	203lm/W	1.5	0.04	75-261-460-5**
14W LED	5700K	2840lm	203lm/W	1.5	0.04	75-262-460-5**
21W LED	5700K	4260lm	203lm/W	1.5	0.04	75-263-460-5**
42W LED	5700K	8520lm	203lm/W	1.5	0.04	75-264-460-5**
** Product colour: 01 (White), 02 (Black), 04 (Grey)						
Options					Add to Ordering Code	
1-10V (analogue) dimming					/AD	
DALI (digital) dimming					/DD	

