

Meadow Lea Waterlooville

Windows

Rehau 70mm double glazed upvc colour white.

Brick

Wienerberger Olde Henfield Multi
Size tolerances, mean and range T1 / R1
Durability F2
Active soluble salts to EN 771-1 S2
Minimum compressive strength $\geq 12 \text{ N/mm}^2$
Maximum Water Absorption $\leq 15 \%$
Pack quantity 500

Feature brick Semi-Engineering brick in Red.

Roof Tile

Mendip Old English Dark Red
Size of Tile
420mm x 330mm

Minimum Pitch
15° Smooth (100mm headlap)
17.5° Smooth (75mm headlap)
30° Granular (75mm headlap)
25° Granular (100mm headlap)
Maximum Pitch
90°
Minimum Headlap
75mm
Maximum Gauge
345mm
Cover Width
298mm (nominal)
Covering Capacity
9.7 tiles /m² at 75mm headlap
10.5 tiles /m² at 100mm headlap
Weight of Tiling
46kg/m² (0.45 Kn/m²) at 75mm headlap
49kg/m² (0.48 Kn/m²) at 100mm headlap
Battens Required
2.9 lin.m/m² at 75mm headlap
3.1 lin.m/m² at 100mm headlap

Batten Size Recommended
38x 25mm for rafters/supports not exceeding 450mm centres
50 x 25mm for rafters/supports not exceeding 600mm centres

Tile Nails
70mm x 3.35mm

Fascia & Soffit

Plastic fascia 20 x 200mm white
plastic timber soffit 25 x 200mm white

Rainwater Goods

Hunter Plastics or similar half round 76mm gutter with associated downpipes in black.