



Roofing

product catalogue

Ashdowne

Handcrafted clay plain tiles offer a warm, mellow appearance, with a granular texture and slight random irregularities that make each tile unique.



Colour availability



Aylesham Mix (F)



Ashurst (F)

Technical data		
Size of tile	265mm x 165mm	
Minimum pitch*	35°	
Maximum pitch	90°	
Minimum headlap	65mm (roof)	35mm (vertical)
Maximum gauge	100mm (roof)	115mm (vertical)
Tile thickness	11mm (nominal)	
Cover width	165mm (nominal)	
Covering capacity (net)	60 tiles/m² at 100mm gauge (roof)	53 tiles/m² at 115mm gauge (vertical)
Weight of tiling (approx.)	65kg/m² (0.64 kN/m²) at 100mm gauge (roof)	57kg/m² (0.56 kN/m²) at 115mm gauge (vertical)
Battens required (net)	10.0 lin.m/m² at 100mm gauge (roof)	8.7 lin.m/m² at 115mm gauge (vertical)
Batten size recommended	38mm x 25mm for rafters/supports not exceeding 600mm centres (fixed to BS 5534)	
Tile nails	38mm x 2.65mm	
Authority	BS EN 1304	

* The minimum recommended pitch and lap may be influenced by special circumstances, please contact the Technical Advisory Service.

Sustainability

- ✓ A+ rated in the BRE Green Guide (based on generic rating for UK produced clay plain tiles Element Ref: 812410006)
- ✓ BES 6001 Responsible Sourcing certified
- ✓ Carbon footprint measurement

Product information

Tile camber
Single camber

Feature tiles
For advice on the use of feature tiles in main roof areas contact the Technical Advisory Service.
† Made to order

Club†

Bullnose†

Hawkins

Single cambered (longitudinal), machine-made clay tile, manufactured for over 150 years. This heritage, combined with modern firing techniques, gives a traditional colour range.



Colour availability



Dark Heather (F)




Staffordshire Blue (F)



Blue Smooth (S)



Staffordshire Mixture (F)



Fired Sienna (T)

Technical data		
Size of tile	265mm x 165mm	
Minimum pitch*	30°	
Maximum pitch	90°	
Minimum headlap	65mm (roof)	35mm (vertical)
Maximum gauge	100mm (roof)	115mm (vertical)
Tile thickness	11mm (nominal)	
Cover width	165mm (nominal)	
Covering capacity (net)	60 tiles/m² at 100mm gauge (roof)	53 tiles/m² at 115mm gauge (vertical)
Weight of tiling (approx.)	64kg/m² (0.63 kN/m²) at 100mm gauge (roof)	56kg/m² (0.55 kN/m²) at 115mm gauge (vertical)
Battens required (net)	10.0 lin.m/m² at 100mm gauge (roof)	8.7 lin.m/m² at 115mm gauge (vertical)
Batten size recommended	38mm x 25mm for rafters/supports not exceeding 600mm centres (fixed to BS 5534)	
Tile nails	38mm x 2.65mm	
Authority	BS EN 1304	

* The minimum recommended pitch and lap may be influenced by special circumstances, please contact the Technical Advisory Service.

Sustainability

- ✓ A+ rated in the BRE Green Guide (based on generic rating for UK produced clay plain tiles Element Ref: 812410006)
- ✓ BES 6001 Responsible Sourcing certified
- ✓ Carbon footprint measurement

Product information

Tile camber
Single camber

Feature tiles
For advice on the use of feature tiles in main roof areas contact the Technical Advisory Service.
† Made to order

Club†

Bullnose†

Call 01283 722588
Email info@marleyeternit.co.uk
Or visit www.marleyeternit.co.uk



Marley Eternit Lichfield Road Branston Burton upon Trent DE14 3HD



an **etex** company