

TYPICAL DETAILS OF ROOFLIGHTS

6 June 2015:

APP
DRG'S
DETAIL

- ① IMAGES VIEW
- ② C/S VIEW
- ③ PHOTOS

1. The Conservation Rooflight, with Ironmongery Option 1b fixed to structural rafter supports 2 at jamb using coach bolts fitted through fixing rail 1c.
2. Structural rafter support at jamb and structural trimmer support at head and cill 2b. Batten bearer for insulation 2c.
3. Insulation fitted on top of structural supports.
4. Timber packers fixed to structural supports 2, 2b to which plasterboard / timber lining is fixed.
5. Plasterboard lining with plasterboard stob 5b to protect corner. Plasterboard fitted behind

to shed rain water.

shedding rain water.

verer exposures) lead flashing at head.
ie 9, 18 and UNDER head membrane 14.
er exposures) lead flashing at cill over tilting fillet 8b.

OR TO installation of the rooflight using a thick continuous bead of
in a position where it will be covered by the cill flange of the rooflight.
roofing membrane 18, UNDER lead flashing 11 and OVER general roofing membrane 8 to ensure suitable lap.
weight as counter battens + top insulation).

the differing nature of installations we strongly advise you to consult your rooflight installer to verify fitness for purpose. This drawing does not constitute a
rooflight purchaser's structural consultant.

