


Modern

A flat, smooth, single lap interlocking design, whose appearance is enhanced by the required broken bond laying pattern.

Colour availability



Anthracite (S)




Smooth Grey (S)



Smooth Brown (S)



Old English Dark Red (S)



Antique Brown (G)



Mosborough Red (S)

Key (G) Granular finish (S) Smooth finish

Technical data

Size of tile	420mm x 330mm
Minimum pitch*	22.5° Smooth (75mm headlap) 17.5° Smooth (100mm headlap)
Maximum pitch	90°
Minimum headlap	75mm
Maximum gauge	345mm
Tile thickness	30mm (nominal)
Cover width	292mm (nominal)
Hanging length	397mm (nominal)
Covering capacity (net)	9.9 tiles/m ² at 75mm headlap
Weight of tiling (approx.)	50kg/m ² (0.49 kN/m ²) at 75mm headlap
Battens required (net)	2.9 lin.m/m ² at 75mm headlap
Batten size recommended	38mm x 25mm for rafters/supports not exceeding 450mm centres (fixed to BS 5534) 50mm x 25mm for rafters/supports not exceeding 600mm centres (fixed to BS 5534)
Tile nails	50mm x 3.35mm
Fixing clips	Eaves, verge and tile clips
Authority	BS EN 490

* The minimum recommended pitch and lap may be influenced by special circumstances, please contact the Technical Advisory Service.


Sustainability

- ✓ A⁺ rated in the BRE Green Guide (based on generic rating for UK produced concrete interlocking tiles
Element Refs: 812410007, 812410018, 812410049)
- ✓ BES 6001 (Responsible Sourcing) certified
- ✓ Carbon footprint measurement

Modern fittings

Available in all colours to match main tiles.

Modern should be laid broken bond. The required broken bond pattern is created by the introduction of half tiles, to form verges in alternate courses. Half tiles are formed on site by cutting along the scoreline.



Note: All measurements in mm.

Duo Modern

A flat, smooth, single lap, interlocking tile with a 'mock bond' joint is enhanced by the required broken bond laying technique.

Colour availability



Old English Dark Red (S)



Smooth Grey (S)

Key (S) Smooth finish

Technical data

Size of tile	420mm x 330mm
Minimum pitch*	22.5° (75mm headlap) 17.5° (100mm headlap)
Maximum pitch	90°
Minimum headlap	75mm
Maximum gauge	345mm
Tile thickness	30mm (nominal)
Cover width	292mm (nominal)
Hanging length	397mm (nominal)
Covering capacity (net)	9.9 tiles/m ² at 75mm headlap
Weight of tiling (approx.)	50kg/m ² (0.49 kN/m ²) at 75mm headlap
Battens required (net)	2.9 lin.m/m ² at 75mm headlap
Batten size recommended	38mm x 25mm for rafters/supports not exceeding 450mm centres (fixed to BS 5534) 50mm x 25mm for rafters/supports not exceeding 600mm centres (fixed to BS 5534)
Tile nails	50mm x 3.35mm
Fixing clips	Eaves, verge and tile clips
Authority	BS EN 490

* The minimum recommended pitch and lap may be influenced by special circumstances, please contact the Technical Advisory Service.

Laying Duo Modern

Duo Modern should be laid quarter bond. The required quarter bond pattern is created by the introduction of three-quarter width tiles, cut from standard tiles on site to form verges in alternate courses.

Sustainability

- ✓ A⁺ rated in the BRE Green Guide (based on generic rating for UK produced concrete interlocking tiles
Element Refs: 812410007, 812410018, 812410049)
- ✓ BES 6001 (Responsible Sourcing) certified
- ✓ Carbon footprint measurement