

Extract Fan		
MUB 042 500E4-A2 Multibox+		
Voltage	230	V
Frequency	50	Hz
Phase	1	~
Input power (P1)	1310	W
Current	5,78	A
Max. airflow	2128	l/s
R.p.m.	1332	r.p.m.
Max. temperature of transported air	40	°C
Sound pressure level at 3 m	56	dB(A)
Weight	64	kg
Insulation class	F	
Enclosure class, motor	54	IP
Capacitor	30	µF

Air input Fan		
MUB 042 450E4-A2 Multibox+		
Voltage	230	V
Frequency	50	Hz
Phase	1	~
Input power (P1)	756	W
Current	3,33	A
Max. airflow	1484	l/s
R.p.m.	1249	r.p.m.
Max. temperature of transported air	60	°C
Max. temperature of transported air when speed-controlled	60	°C
Sound pressure level at 1 m	52	dB(A)
Weight	54	kg
Insulation class	F	
Enclosure class, motor	54	IP
Capacitor	16	µF

100MM THICK 4 SIDED ACOUSTIC ENCLOSURE WITH 100MM THICK LID			
Noise reduction approximately	15 dB(a)	2 Off	
Weight	100 Kg		
Odour control carbon filter box		1 off	
Weight complete with filters	200 Kg		

Air Conditioning external units	5 off Plus cold room		
OUTDOOR			
Sound Pressure Level (dBA) Heating / Cooling	48 / 47		
Sound Power Level (dBA) Cooling	58		
Weight (kg)	30		
Dimensions (mm) Width x Depth x Height	800 x 285 x 550		
Electrical Supply	220-240V, 50HZ		
Phase	SINGLE		
System Power Input (kW) - Heating / Cooling (nominal)	0.80 / 0.73		
System Power Input (kW) - Heating / Cooling (UK)	0.71 / 0.62		
Starting Current (A)	3.8		
System Running Current (A) [MAX] - Heating / Cooling	3.50 / 3.80 [7.4]		
Fuse Rating (BS88) - HRC (A)	10		
Mains Cable No. Cores	3		
Max Pipe Length (m)	20		
Max Height Difference (m)	12		
Charge R410A (kg) - Pre charged length (m)	0.8 - 7		