

Model No.	Indoor unit		AUYG30LRLE	
	Outdoor unit		AOYG30LETL	
Power Source			V/ Ø/Hz 230/1/50	
Capacity	Cooling	kW	8.5 (2.8-10.0)	
	Heating		10.0 (2.7-11.2)	
Input Power	Cooling/Heating	kW	2.65/2.77	
EER	Cooling	W/W	3.21	
COP	Heating		3.61	
Pdesign	Cooling/Heating	kW	8.5/8.0	
SEER	Cooling	W/W	6.50	
SCOP	Heating		4.30	
Energy Efficiency Class	Cooling		A++	
	Heating		A+	
Running Current	Cooling/Heating	A	11.6/12.2	
Annual Energy Consumption	Cooling	kWh/a	458	
	Heating		2604	
Moisture Removal			l/h 2.5	
Sound Pressure (Cooling)	Indoor	H/M/L/Q	dB(A)	40/38/36/32
	Outdoor	High		53
Sound Power (Cooling)	Indoor	High		54
	Outdoor	High		68
Airflow Rate (High)	Indoor / Outdoor		m³/h	1600/3600
Net Dimension H x W x D	Indoor		mm	288x840x840 50x950x950
			kg(lbs)	26 (57) / 5.5 (12)
	Outdoor		mm	830x900x330
			kg(lbs)	61 (135)
Piping Connections (Small / Large)			mm	9.52/15.88
Drain Hose Diameter (I.D./O.D.)				25.0/32.0
Max Pipe Length (Pre-Charge)			m	50 (20)
Max Height Difference				30
Operation Range	Cooling	°CDB	-15 to 46	
	Heating		-15 to 24	
Refrigerant (Global Warming Potential)				R410A (1,975)
Cassette Grille				UTG-UGYA-W