



- NOTES:
1. Do not scale from this drawing.
 2. All dimensions in metres and all levels relate to Ordnance Datum.
 3. This drawing is to be read in conjunction with all other engineering drawings. Any discrepancies shall be reported to MJA Consulting Engineer's.
 4. The level and location of all existing services shall be verified on site by the Contractor before commencing any construction work.
 5. All section 104 work shall be in accordance with the document "Sewers for Adoption" 6th Edition as published by WRC plc together with relevant Water Authority requirements.
 6. All adoptable works to be checked by the Water Authority Inspector.
 7. All adoptable pipework up to DN225 shall be Extra Strength Vitrified Clay, DN300 or above shall be concrete. All adoptable pipes to be Strength Class 120. If the contractor wishes to use structural wall plastic pipe, then approval must be gained from the Adopting Water Authority.
 8. Sewers and drains of different diameters should be laid soffit to soffit unless otherwise specified.
 9. All covers and frames shall be 150mm deep to BS.EN.124, badged SW or FW if requested.
 10. Contractor must comply with all current legislation relating to CDM, Health and Safety and COSHH.

HAVANT BOROUGH
COUNCIL
10 JAN 2014
RECEIVED

PRELIMINARY

B	14.06.13	FWS msholme invert levels revised. FWS msholme added to roads 384.		JOK
A	24.06.13	Foul msholme F16 & F24 removed		KTG
REV	NO	DATE	DESCRIPTION	INITIALS
Client				
				
BARATT & PARTNERS CIVIL & STRUCTURAL ENGINEERS		MJA CONSULTING CIVIL AND STRUCTURAL ENGINEERS		
Project Manor Farm Denwilles		58-62 Cook Street, Abingdon Oxon, OX14 5BZ Tel: 01235 559173 Fax: 01235 532226		
				
Title Longitudinal Sections		Drawing No. 4527:10		
Scale A3: shown@A0 Checked KTG Drawn WSP		Date Feb '13 Date 10/02/13		
		Rev B		