

Junctions 8
PICADY 8 - Priority Intersection Module
Version: 8.0.2.316 [14 Feb 2013] © Copyright TRL Limited, 2013
For sales and distribution information, program advice and maintenance, contact TRL: Tel: +44 (0)1344 770758 E-mail: software@trl.co.uk Web: http://www.trlsoftware.co.uk
The users of this computer program for the solution of an engineering problem are in no way relieved of their responsibility for the correctness of the solution

Filename: 06. Milton Road_Durley Avenue Junction.arc8

Path: J:\21834 Woodcroft Farm\004 Transport\Working Documents\Junction Analysis\PICADY\April 2013 Assessments

Report generation date: 08/07/2013 10:10:38

-
- » Existing Layout - 2010 Observed, AM
 - » Existing Layout - 2010 Observed, PM
 - » Existing Layout - 2018 Baseline, AM
 - » Existing Layout - 2018 Baseline, PM
 - » Existing Layout - 2018 Baseline + Dev, AM
 - » Existing Layout - 2018 Baseline + Dev, PM

Summary of junction performance

	AM				PM			
	Queue (PCU)	Delay (s)	RFC	LOS	Queue (PCU)	Delay (s)	RFC	LOS
Existing Layout - 2010 Observed								
Stream B-AC	0.20	9.45	0.17	A	0.26	12.17	0.20	B
Stream C-AB	0.22	5.94	0.12	A	0.70	4.88	0.25	A
Stream C-A	-	-	-	-	-	-	-	-
Stream A-B	-	-	-	-	-	-	-	-
Stream A-C	-	-	-	-	-	-	-	-
Existing Layout - 2018 Baseline								
Stream B-AC	0.25	10.32	0.20	B	0.32	13.50	0.24	B
Stream C-AB	0.28	6.05	0.14	A	0.94	5.11	0.31	A
Stream C-A	-	-	-	-	-	-	-	-
Stream A-B	-	-	-	-	-	-	-	-
Stream A-C	-	-	-	-	-	-	-	-
Existing Layout - 2018 Baseline + Dev								
Stream B-AC	0.26	10.59	0.20	B	0.33	14.02	0.25	B
Stream C-AB	0.29	6.07	0.14	A	1.01	5.11	0.32	A
Stream C-A	-	-	-	-	-	-	-	-
Stream A-B	-	-	-	-	-	-	-	-
Stream A-C	-	-	-	-	-	-	-	-

Values shown are the maximum values over all time segments. Delay is the maximum value of average delay per arriving vehicle.

'D1 - 2010 Observed, AM" model duration: 08:00 - 09:00

'D2 - 2010 Observed, PM" model duration: 17:00 - 18:00

'D3 - 2018 Baseline, AM" model duration: 08:00 - 09:00

'D4 - 2018 Baseline, PM" model duration: 17:00 - 18:00

'D5 - 2018 Baseline + Dev, AM" model duration: 08:00 - 09:00

'D6 - 2018 Baseline + Dev, PM" model duration: 17:00 - 18:00

'D7 - 2023 Baseline, AM" model duration: 08:00 - 09:00

'D8 - 2023 Baseline, PM" model duration: 17:00 - 18:00

'D9 - 2023 Baseline + Dev, AM" model duration: 08:00 - 09:00

'D10 - 2023 Baseline + Dev, PM" model duration: 17:00 - 18:00

'D11 - 2023 Baseline + Dev (700 Units), AM" model duration: 08:00 - 09:00

'D12 - 2023 Baseline + Dev (700 Units), PM" model duration: 17:00 - 18:00

'D13 - 2018 Baseline + Dev (700 Units), AM" model duration: 08:00 - 09:00

'D14 - 2018 Baseline + Dev (700 Units), PM" model duration: 17:00 - 18:00

Run using Junctions 8.0.2.316 at 08/07/2013 10:10:34

File summary

File Description

Title	Milton Road_Durley Avenue Junction
Location	Waterlooville
Site Number	06
Date	15/04/2013
Version	
Status	(new file)
Identifier	
Client	
Jobnumber	21834
Enumerator	
Description	

Analysis Options

Vehicle Length (m)	Do Queue Variations	Calculate Residual Capacity	Residual Capacity Criteria Type	RFC Threshold	Average Delay Threshold (s)	Queue Threshold (PCU)
5.75			N/A	0.85	36.00	20.00

Units

Distance Units	Speed Units	Traffic Units Input	Traffic Units Results	Flow Units	Average Delay Units	Total Delay Units	Rate Of Delay Units
m	kph	PCU	PCU	perHour	s	-Min	perMin

Existing Layout - 2010 Observed, AM

Data Errors and Warnings

No errors or warnings

Analysis Set Details

Name	Roundabout Capacity Model	Description	Include In Report	Use Specific Demand Set (s)	Specific Demand Set(s)	Locked	Network Flow Scaling Factor (%)	Network Capacity Scaling Factor (%)	Reason For Scaling Factors
Existing Layout	N/A		✓	✓	D1,D2,D3,D4,D5,D6		100.000	100.000	

Demand Set Details

Name	Scenario Name	Time Period Name	Description	Traffic Profile Type	Model Start Time (HH:mm)	Model Finish Time (HH:mm)	Model Time Period Length (min)	Time Segment Length (min)	Results For Central Hour Only	Single Time Segment Only	Locked	Run Automatically	Use Relationship	Rela
2010 Observed, AM	2010 Observed	AM		DIRECT	08:00	09:00	60	15				✓		

Junction Network

Junctions

Name	Junction Type	Major Road Direction	Arm Order	Do Geometric Delay	Junction Delay (s)	Junction LOS
Milton Road_Durley Avenue Junction	T-Junction	Two-way	A,B,C		7.66	A

Junction Network Options

Driving Side	Lighting
Left	Normal/unknown

Arms

Arms

Arm	Name	Description	Arm Type
A	Milton Road (N)		Major
B	Durley Avenue		Minor
C	Milton Road (S)		Major

Major Arm Geometry

Arm	Width of carriageway (m)	Has kerbed central reserve	Width of kerbed central reserve (m)	Has right turn bay	Width For Right Turn (m)	Visibility For Right Turn (m)	Blocks?	Blocking Queue (PCU)
C	6.70		0.00		2.20	160.00	✓	0.00

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Minor Arm Geometry

Arm	Minor Arm Type	Lane Width (m)	Lane Width (Left) (m)	Lane Width (Right) (m)	Width at give-way (m)	Width at 5m (m)	Width at 10m (m)	Width at 15m (m)	Width at 20m (m)	Estimate Flare Length	Flare Length (PCU)	Visibility To Left (m)	Visibility To Right (m)
B	One lane	2.75										40	39

Pedestrian Crossings

Arm	Crossing Type
A	None
B	None
C	None

Slope / Intercept / Capacity

Priority Intersection Slopes and Intercepts

Junction	Stream	Intercept (PCU/hr)	Slope for A-B	Slope for A-C	Slope for C-A	Slope for C-B
06	B-A	496.995	0.088	0.222	0.140	0.317
06	B-C	632.257	0.094	0.238	-	-
06	C-B	666.621	0.250	0.250	-	-

The slopes and intercepts shown above do NOT include any corrections or adjustments.

Streams may be combined, in which case capacity will be adjusted.

Values are shown for the first time segment only; they may differ for subsequent time segments.

Traffic Flows

Demand Set Data Options

Default Vehicle Mix	Vehicle Mix Varies Over Time	Vehicle Mix Varies Over Turn	Vehicle Mix Varies Over Entry	Vehicle Mix Source	PCU Factor for a HV (PCU)	Default Turning Proportions	Estimate from entry/exit counts	Turning Proportions Vary Over Time	Turning Proportions Vary Over Turn	Turning Proportions Vary Over Entry
		✓	✓	HV Percentages	2.00				✓	✓

Entry Flows

General Flows Data

Arm	Profile Type	Use Turning Counts	Average Demand Flow (PCU/hr)	Flow Scaling Factor (%)
A	DIRECT	✓	N/A	100.000
B	DIRECT	✓	N/A	100.000
C	DIRECT	✓	N/A	100.000

Turning Proportions

Turning Counts or Proportions (PCU/hr) - Junction 06 (for whole period)

		To		
		A	B	C
From	A	0.000	38.000	644.000
	B	5.000	0.000	72.000
	C	264.000	49.000	0.000

Turning Proportions (PCU) - Junction 06 (for whole period)

		To		
		A	B	C
From	A	0.00	0.06	0.94
	B	0.06	0.00	0.94
	C	0.84	0.16	0.00

Vehicle Mix

Average PCU Per Vehicle - Junction 06 (for whole period)

		To		
		A	B	C
From	A	1.000	1.000	1.000
	B	1.000	1.000	1.000
	C	1.000	1.000	1.000

Heavy Vehicle Percentages - Junction 06 (for whole period)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)	Total Queueing Delay (PCU-min)	Average Queueing Delay (s)	Rate Of Queueing Delay (PCU-min/min)	Inclusive Total Queueing Delay (PCU-min)	Inclusive Average Queueing Delay (s)
B-AC	0.17	9.45	0.20	A	77.00	77.00	11.91	9.28	0.20	11.91	9.28
C-AB	0.12	5.94	0.22	A	79.51	79.51	12.95	9.78	0.22	12.96	9.78
C-A	-	-	-	-	233.49	233.49	-	-	-	-	-
A-B	-	-	-	-	38.00	38.00	-	-	-	-	-
A-C	-	-	-	-	644.00	644.00	-	-	-	-	-

Existing Layout - 2010 Observed, PM

Data Errors and Warnings

No errors or warnings

Analysis Set Details

Name	Roundabout Capacity Model	Description	Include In Report	Use Specific Demand Set (s)	Specific Demand Set(s)	Locked	Network Flow Scaling Factor (%)	Network Capacity Scaling Factor (%)	Reason For Scaling Factors
Existing Layout	N/A		✓	✓	D1,D2,D3,D4,D5,D6		100.000	100.000	

Demand Set Details

Name	Scenario Name	Time Period Name	Description	Traffic Profile Type	Model Start Time (HH:mm)	Model Finish Time (HH:mm)	Model Time Period Length (min)	Time Segment Length (min)	Results For Central Hour Only	Single Time Segment Only	Locked	Run Automatically	Use Relationship	Rela
2010 Observed, PM	2010 Observed	PM		DIRECT	17:00	18:00	60	15				✓		

Junction Network

Junctions

Name	Junction Type	Major Road Direction	Arm Order	Do Geometric Delay	Junction Delay (s)	Junction LOS
Milton Road_Durley Avenue Junction	T-Junction	Two-way	A,B,C		6.59	A

Junction Network Options

Driving Side	Lighting
Left	Normal/unknown

Arms

Arms

Arm	Name	Description	Arm Type
A	Milton Road (N)		Major
B	Durley Avenue		Minor
C	Milton Road (S)		Major

Major Arm Geometry

Arm	Width of carriageway (m)	Has kerbed central reserve	Width of kerbed central reserve (m)	Has right turn bay	Width For Right Turn (m)	Visibility For Right Turn (m)	Blocks?	Blocking Queue (PCU)
C	6.70		0.00		2.20	160.00	✓	0.00

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Minor Arm Geometry

Arm	Minor Arm Type	Lane Width (m)	Lane Width (Left) (m)	Lane Width (Right) (m)	Width at give-way (m)	Width at 5m (m)	Width at 10m (m)	Width at 15m (m)	Width at 20m (m)	Estimate Flare Length	Flare Length (PCU)	Visibility To Left (m)	Visibility To Right (m)
B	One lane	2.75										40	39

Pedestrian Crossings

Arm	Crossing Type
A	None
B	None
C	None

Slope / Intercept / Capacity

Priority Intersection Slopes and Intercepts

Junction	Stream	Intercept (PCU/hr)	Slope for A-B	Slope for A-C	Slope for C-A	Slope for C-B
06	B-A	496.995	0.088	0.222	0.140	0.317
06	B-C	632.257	0.094	0.238	-	-
06	C-B	666.621	0.250	0.250	-	-

The slopes and intercepts shown above do NOT include any corrections or adjustments.

Streams may be combined, in which case capacity will be adjusted.

Values are shown for the first time segment only; they may differ for subsequent time segments.

Traffic Flows

Demand Set Data Options

Default Vehicle Mix	Vehicle Mix Varies Over Time	Vehicle Mix Varies Over Turn	Vehicle Mix Varies Over Entry	Vehicle Mix Source	PCU Factor for a HV (PCU)	Default Turning Proportions	Estimate from entry/exit counts	Turning Proportions Vary Over Time	Turning Proportions Vary Over Turn	Turning Proportions Vary Over Entry
		✓	✓	HV Percentages	2.00				✓	✓

Entry Flows

General Flows Data

Arm	Profile Type	Use Turning Counts	Average Demand Flow (PCU/hr)	Flow Scaling Factor (%)
A	DIRECT	✓	N/A	100.000
B	DIRECT	✓	N/A	100.000
C	DIRECT	✓	N/A	100.000

Turning Proportions

Turning Counts or Proportions (PCU/hr) - Junction 06 (for whole period)

	To			
From		A	B	C
	A	0.000	39.000	430.000
	B	36.000	0.000	40.000
	C	637.000	90.000	0.000

Turning Proportions (PCU) - Junction 06 (for whole period)

	To			
		A	B	C
From	A	0.00	0.08	0.92
	B	0.47	0.00	0.53
	C	0.88	0.12	0.00

Vehicle Mix

Average PCU Per Vehicle - Junction 06 (for whole period)

	To			
		A	B	C
From	A	1.000	1.000	1.000
	B	1.000	1.000	1.000
	C	1.000	1.000	1.000

Heavy Vehicle Percentages - Junction 06 (for whole period)

	To			
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)	Total Queueing Delay (PCU-min)	Average Queueing Delay (s)	Rate Of Queueing Delay (PCU-min/min)	Inclusive Total Queueing Delay (PCU-min)	Inclusive Average Queueing Delay (s)
B-AC	0.20	12.17	0.26	B	76.00	76.00	15.06	11.89	0.25	15.06	11.89
C-AB	0.25	4.88	0.70	A	247.95	247.95	41.64	10.08	0.69	41.65	10.08
C-A	-	-	-	-	479.05	479.05	-	-	-	-	-
A-B	-	-	-	-	39.00	39.00	-	-	-	-	-
A-C	-	-	-	-	430.00	430.00	-	-	-	-	-

Existing Layout - 2018 Baseline, AM

Data Errors and Warnings

No errors or warnings

Analysis Set Details

Name	Roundabout Capacity Model	Description	Include In Report	Use Specific Demand Set (s)	Specific Demand Set(s)	Locked	Network Flow Scaling Factor (%)	Network Capacity Scaling Factor (%)	Reason For Scaling Factors
Existing Layout	N/A		✓	✓	D1,D2,D3,D4,D5,D6		100.000	100.000	

Demand Set Details

Name	Scenario Name	Time Period Name	Description	Traffic Profile Type	Model Start Time (HH:mm)	Model Finish Time (HH:mm)	Model Time Period Length (min)	Time Segment Length (min)	Results For Central Hour Only	Single Time Segment Only	Locked	Run Automatically	Use Relationship	Relative
2018 Baseline, AM	2018 Baseline	AM		DIRECT	08:00	09:00	60	15				✓		

Junction Network

Junctions

Name	Junction Type	Major Road Direction	Arm Order	Do Geometric Delay	Junction Delay (s)	Junction LOS
Milton Road_Durley Avenue Junction	T-Junction	Two-way	A,B,C		8.08	A

Junction Network Options

Driving Side	Lighting
Left	Normal/unknown

Arms

Arms

Arm	Name	Description	Arm Type
A	Milton Road (N)		Major
B	Durley Avenue		Minor
C	Milton Road (S)		Major

Major Arm Geometry

Arm	Width of carriageway (m)	Has kerbed central reserve	Width of kerbed central reserve (m)	Has right turn bay	Width For Right Turn (m)	Visibility For Right Turn (m)	Blocks?	Blocking Queue (PCU)
C	6.70		0.00		2.20	160.00	✓	0.00

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Minor Arm Geometry

Arm	Minor Arm Type	Lane Width (m)	Lane Width (Left) (m)	Lane Width (Right) (m)	Width at give-way (m)	Width at 5m (m)	Width at 10m (m)	Width at 15m (m)	Width at 20m (m)	Estimate Flare Length	Flare Length (PCU)	Visibility To Left (m)	Visibility To Right (m)
B	One lane	2.75										40	39

Pedestrian Crossings

Arm	Crossing Type
A	None
B	None
C	None

Slope / Intercept / Capacity

Priority Intersection Slopes and Intercepts

Junction	Stream	Intercept (PCU/hr)	Slope for A-B	Slope for A-C	Slope for C-A	Slope for C-B
06	B-A	496.995	0.088	0.222	0.140	0.317
06	B-C	632.257	0.094	0.238	-	-
06	C-B	666.621	0.250	0.250	-	-

The slopes and intercepts shown above do NOT include any corrections or adjustments.

Streams may be combined, in which case capacity will be adjusted.

Values are shown for the first time segment only; they may differ for subsequent time segments.

Traffic Flows

Demand Set Data Options

Default Vehicle Mix	Vehicle Mix Varies Over Time	Vehicle Mix Varies Over Turn	Vehicle Mix Varies Over Entry	Vehicle Mix Source	PCU Factor for a HV (PCU)	Default Turning Proportions	Estimate from entry/exit counts	Turning Proportions Vary Over Time	Turning Proportions Vary Over Turn	Turning Proportions Vary Over Entry
		✓	✓	HV Percentages	2.00				✓	✓

Entry Flows

General Flows Data

Arm	Profile Type	Use Turning Counts	Average Demand Flow (PCU/hr)	Flow Scaling Factor (%)
A	DIRECT	✓	N/A	100.000
B	DIRECT	✓	N/A	100.000
C	DIRECT	✓	N/A	100.000

Turning Proportions

Turning Counts or Proportions (PCU/hr) - Junction 06 (for whole period)

	To			
From		A	B	C
	A	0.000	43.000	726.000
	B	6.000	0.000	81.000
	C	297.000	55.000	0.000

Source: Junctions 8 (8.0.2.316) - Junction 06 (for whole period)

Turning Proportions (PCU) - Junction 06 (for whole period)

	To			
		A	B	C
From	A	0.00	0.06	0.94
	B	0.07	0.00	0.93
	C	0.84	0.16	0.00

Vehicle Mix

Average PCU Per Vehicle - Junction 06 (for whole period)

	To			
		A	B	C
From	A	1.000	1.000	1.000
	B	1.000	1.000	1.000
	C	1.000	1.000	1.000

Heavy Vehicle Percentages - Junction 06 (for whole period)

	To			
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)	Total Queueing Delay (PCU-min)	Average Queueing Delay (s)	Rate Of Queueing Delay (PCU-min/min)	Inclusive Total Queueing Delay (PCU-min)	Inclusive Average Queueing Delay (s)
B-AC	0.20	10.32	0.25	B	87.00	87.00	14.67	10.12	0.24	14.68	10.12
C-AB	0.14	6.05	0.28	A	96.08	96.08	16.62	10.38	0.28	16.62	10.38
C-A	-	-	-	-	255.92	255.92	-	-	-	-	-
A-B	-	-	-	-	43.00	43.00	-	-	-	-	-
A-C	-	-	-	-	726.00	726.00	-	-	-	-	-

Existing Layout - 2018 Baseline, PM

Data Errors and Warnings

No errors or warnings

Analysis Set Details

Name	Roundabout Capacity Model	Description	Include In Report	Use Specific Demand Set (s)	Specific Demand Set(s)	Locked	Network Flow Scaling Factor (%)	Network Capacity Scaling Factor (%)	Reason For Scaling Factors
Existing Layout	N/A		✓	✓	D1,D2,D3,D4,D5,D6		100.000	100.000	

Demand Set Details

Name	Scenario Name	Time Period Name	Description	Traffic Profile Type	Model Start Time (HH:mm)	Model Finish Time (HH:mm)	Model Time Period Length (min)	Time Segment Length (min)	Results For Central Hour Only	Single Time Segment Only	Locked	Run Automatically	Use Relationship	Relative
2018 Baseline, PM	2018 Baseline	PM		DIRECT	17:00	18:00	60	15				✓		

Junction Network

Junctions

Name	Junction Type	Major Road Direction	Arm Order	Do Geometric Delay	Junction Delay (s)	Junction LOS
Milton Road_Durley Avenue Junction	T-Junction	Two-way	A,B,C		6.89	A

Junction Network Options

Driving Side	Lighting
Left	Normal/unknown

Arms

Arms

Arm	Name	Description	Arm Type
A	Milton Road (N)		Major
B	Durley Avenue		Minor
C	Milton Road (S)		Major

Major Arm Geometry

Arm	Width of carriageway (m)	Has kerbed central reserve	Width of kerbed central reserve (m)	Has right turn bay	Width For Right Turn (m)	Visibility For Right Turn (m)	Blocks?	Blocking Queue (PCU)
C	6.70		0.00		2.20	160.00	✓	0.00

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Minor Arm Geometry

Arm	Minor Arm Type	Lane Width (m)	Lane Width (Left) (m)	Lane Width (Right) (m)	Width at give-way (m)	Width at 5m (m)	Width at 10m (m)	Width at 15m (m)	Width at 20m (m)	Estimate Flare Length	Flare Length (PCU)	Visibility To Left (m)	Visibility To Right (m)
B	One lane	2.75										40	39

Pedestrian Crossings

Arm	Crossing Type
A	None
B	None
C	None

Slope / Intercept / Capacity

Priority Intersection Slopes and Intercepts

Junction	Stream	Intercept (PCU/hr)	Slope for A-B	Slope for A-C	Slope for C-A	Slope for C-B
06	B-A	496.995	0.088	0.222	0.140	0.317
06	B-C	632.257	0.094	0.238	-	-
06	C-B	666.621	0.250	0.250	-	-

The slopes and intercepts shown above do NOT include any corrections or adjustments.

Streams may be combined, in which case capacity will be adjusted.

Values are shown for the first time segment only; they may differ for subsequent time segments.

Traffic Flows

Demand Set Data Options

Default Vehicle Mix	Vehicle Mix Varies Over Time	Vehicle Mix Varies Over Turn	Vehicle Mix Varies Over Entry	Vehicle Mix Source	PCU Factor for a HV (PCU)	Default Turning Proportions	Estimate from entry/exit counts	Turning Proportions Vary Over Time	Turning Proportions Vary Over Turn	Turning Proportions Vary Over Entry
		✓	✓	HV Percentages	2.00				✓	✓

Entry Flows

General Flows Data

Arm	Profile Type	Use Turning Counts	Average Demand Flow (PCU/hr)	Flow Scaling Factor (%)
A	DIRECT	✓	N/A	100.000
B	DIRECT	✓	N/A	100.000
C	DIRECT	✓	N/A	100.000

Turning Proportions

Turning Counts or Proportions (PCU/hr) - Junction 06 (for whole period)

	To			
From		A	B	C
	A	0.000	44.000	470.000
	B	40.000	0.000	45.000
	C	695.000	102.000	0.000

[Back](#)
[Home](#)
[Junctions](#)
[Junction 06](#)
[Junction 07](#)
[Junction 08](#)
[Junction 09](#)
[Junction 10](#)
[Junction 11](#)
[Junction 12](#)
[Junction 13](#)
[Junction 14](#)
[Junction 15](#)
[Junction 16](#)
[Junction 17](#)
[Junction 18](#)
[Junction 19](#)
[Junction 20](#)
[Junction 21](#)
[Junction 22](#)
[Junction 23](#)
[Junction 24](#)
[Junction 25](#)
[Junction 26](#)
[Junction 27](#)
[Junction 28](#)
[Junction 29](#)
[Junction 30](#)
[Junction 31](#)
[Junction 32](#)
[Junction 33](#)
[Junction 34](#)
[Junction 35](#)
[Junction 36](#)
[Junction 37](#)
[Junction 38](#)
[Junction 39](#)
[Junction 40](#)
[Junction 41](#)
[Junction 42](#)
[Junction 43](#)
[Junction 44](#)
[Junction 45](#)
[Junction 46](#)
[Junction 47](#)
[Junction 48](#)
[Junction 49](#)
[Junction 50](#)
[Junction 51](#)
[Junction 52](#)
[Junction 53](#)
[Junction 54](#)
[Junction 55](#)
[Junction 56](#)
[Junction 57](#)
[Junction 58](#)
[Junction 59](#)
[Junction 60](#)
[Junction 61](#)
[Junction 62](#)
[Junction 63](#)
[Junction 64](#)
[Junction 65](#)
[Junction 66](#)
[Junction 67](#)
[Junction 68](#)
[Junction 69](#)
[Junction 70](#)
[Junction 71](#)
[Junction 72](#)
[Junction 73](#)
[Junction 74](#)
[Junction 75](#)
[Junction 76](#)
[Junction 77](#)
[Junction 78](#)
[Junction 79](#)
[Junction 80](#)
[Junction 81](#)
[Junction 82](#)
[Junction 83](#)
[Junction 84](#)
[Junction 85](#)
[Junction 86](#)
[Junction 87](#)
[Junction 88](#)
[Junction 89](#)
[Junction 90](#)
[Junction 91](#)
[Junction 92](#)
[Junction 93](#)
[Junction 94](#)
[Junction 95](#)
[Junction 96](#)
[Junction 97](#)
[Junction 98](#)
[Junction 99](#)

Turning Proportions (PCU) - Junction 06 (for whole period)

	To			
		A	B	C
From	A	0.00	0.09	0.91
	B	0.47	0.00	0.53
	C	0.87	0.13	0.00

Vehicle Mix

Average PCU Per Vehicle - Junction 06 (for whole period)

	To			
		A	B	C
From	A	1.000	1.000	1.000
	B	1.000	1.000	1.000
	C	1.000	1.000	1.000

Heavy Vehicle Percentages - Junction 06 (for whole period)

	To			
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)	Total Queueing Delay (PCU-min)	Average Queueing Delay (s)	Rate Of Queueing Delay (PCU-min/min)	Inclusive Total Queueing Delay (PCU-min)	Inclusive Average Queueing Delay (s)
B-AC	0.24	13.50	0.32	B	85.00	85.00	18.61	13.14	0.31	18.62	13.14
C-AB	0.31	5.11	0.94	A	315.37	315.37	56.21	10.69	0.94	56.23	10.70
C-A	-	-	-	-	481.63	481.63	-	-	-	-	-
A-B	-	-	-	-	44.00	44.00	-	-	-	-	-
A-C	-	-	-	-	470.00	470.00	-	-	-	-	-

Existing Layout - 2018 Baseline + Dev, AM

Data Errors and Warnings

No errors or warnings

Analysis Set Details

Name	Roundabout Capacity Model	Description	Include In Report	Use Specific Demand Set (s)	Specific Demand Set(s)	Locked	Network Flow Scaling Factor (%)	Network Capacity Scaling Factor (%)	Reason For Scaling Factors
Existing Layout	N/A		✓	✓	D1,D2,D3,D4,D5,D6		100.000	100.000	

Demand Set Details

Name	Scenario Name	Time Period Name	Description	Traffic Profile Type	Model Start Time (HH:mm)	Model Finish Time (HH:mm)	Model Time Period Length (min)	Time Segment Length (min)	Results For Central Hour Only	Single Time Segment Only	Locked	Run Automatically	Use Relationship	Relatio
2018 Baseline + Dev, AM	2018 Baseline + Dev	AM		DIRECT	08:00	09:00	60	15				✓		

Junction Network

Junctions

Name	Junction Type	Major Road Direction	Arm Order	Do Geometric Delay	Junction Delay (s)	Junction LOS
Milton Road_Durley Avenue Junction	T-Junction	Two-way	A,B,C		8.19	A

Junction Network Options

Driving Side	Lighting
Left	Normal/unknown

Arms

Arms

Arm	Name	Description	Arm Type
A	Milton Road (N)		Major
B	Durley Avenue		Minor
C	Milton Road (S)		Major

Major Arm Geometry

Arm	Width of carriageway (m)	Has kerbed central reserve	Width of kerbed central reserve (m)	Has right turn bay	Width For Right Turn (m)	Visibility For Right Turn (m)	Blocks?	Blocking Queue (PCU)
C	6.70		0.00		2.20	160.00	✓	0.00

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Minor Arm Geometry

Arm	Minor Arm Type	Lane Width (m)	Lane Width (Left) (m)	Lane Width (Right) (m)	Width at give-way (m)	Width at 5m (m)	Width at 10m (m)	Width at 15m (m)	Width at 20m (m)	Estimate Flare Length	Flare Length (PCU)	Visibility To Left (m)	Visibility To Right (m)
B	One lane	2.75										40	39

Pedestrian Crossings

Arm	Crossing Type
A	None
B	None
C	None

Slope / Intercept / Capacity

Priority Intersection Slopes and Intercepts

Junction	Stream	Intercept (PCU/hr)	Slope for A-B	Slope for A-C	Slope for C-A	Slope for C-B
06	B-A	496.995	0.088	0.222	0.140	0.317
06	B-C	632.257	0.094	0.238	-	-
06	C-B	666.621	0.250	0.250	-	-

The slopes and intercepts shown above do NOT include any corrections or adjustments.

Streams may be combined, in which case capacity will be adjusted.

Values are shown for the first time segment only; they may differ for subsequent time segments.

Traffic Flows

Demand Set Data Options

Default Vehicle Mix	Vehicle Mix Varies Over Time	Vehicle Mix Varies Over Turn	Vehicle Mix Varies Over Entry	Vehicle Mix Source	PCU Factor for a HV (PCU)	Default Turning Proportions	Estimate from entry/exit counts	Turning Proportions Vary Over Time	Turning Proportions Vary Over Turn	Turning Proportions Vary Over Entry
		✓	✓	HV Percentages	2.00				✓	✓

Entry Flows

General Flows Data

Arm	Profile Type	Use Turning Counts	Average Demand Flow (PCU/hr)	Flow Scaling Factor (%)
A	DIRECT	✓	N/A	100.000
B	DIRECT	✓	N/A	100.000
C	DIRECT	✓	N/A	100.000

Turning Proportions

Turning Counts or Proportions (PCU/hr) - Junction 06 (for whole period)

	To			
From		A	B	C
	A	0.000	44.000	761.000
	B	6.000	0.000	81.000
	C	308.000	55.000	0.000

Turning Proportions (PCU) - Junction 06 (for whole period)

	To			
		A	B	C
From	A	0.00	0.05	0.95
	B	0.07	0.00	0.93
	C	0.85	0.15	0.00

Vehicle Mix

Average PCU Per Vehicle - Junction 06 (for whole period)

	To			
		A	B	C
From	A	1.000	1.000	1.000
	B	1.000	1.000	1.000
	C	1.000	1.000	1.000

Heavy Vehicle Percentages - Junction 06 (for whole period)

	To			
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)	Total Queueing Delay (PCU-min)	Average Queueing Delay (s)	Rate Of Queueing Delay (PCU-min/min)	Inclusive Total Queueing Delay (PCU-min)	Inclusive Average Queueing Delay (s)
B-AC	0.20	10.59	0.26	B	87.00	87.00	15.05	10.38	0.25	15.05	10.38
C-AB	0.14	6.07	0.29	A	98.71	98.71	17.50	10.64	0.29	17.50	10.64
C-A	-	-	-	-	264.29	264.29	-	-	-	-	-
A-B	-	-	-	-	44.00	44.00	-	-	-	-	-
A-C	-	-	-	-	761.00	761.00	-	-	-	-	-

Existing Layout - 2018 Baseline + Dev, PM

Data Errors and Warnings

No errors or warnings

Analysis Set Details

Name	Roundabout Capacity Model	Description	Include In Report	Use Specific Demand Set (s)	Specific Demand Set(s)	Locked	Network Flow Scaling Factor (%)	Network Capacity Scaling Factor (%)	Reason For Scaling Factors
Existing Layout	N/A		✓	✓	D1,D2,D3,D4,D5,D6		100.000	100.000	

Demand Set Details

Name	Scenario Name	Time Period Name	Description	Traffic Profile Type	Model Start Time (HH:mm)	Model Finish Time (HH:mm)	Model Time Period Length (min)	Time Segment Length (min)	Results For Central Hour Only	Single Time Segment Only	Locked	Run Automatically	Use Relationship	Relatio
2018 Baseline + Dev, PM	2018 Baseline + Dev	PM		DIRECT	17:00	18:00	60	15				✓		

Junction Network

Junctions

Name	Junction Type	Major Road Direction	Arm Order	Do Geometric Delay	Junction Delay (s)	Junction LOS
Milton Road_Durley Avenue Junction	T-Junction	Two-way	A,B,C		6.95	A

Junction Network Options

Driving Side	Lighting
Left	Normal/unknown

Arms

Arms

Arm	Name	Description	Arm Type
A	Milton Road (N)		Major
B	Durley Avenue		Minor
C	Milton Road (S)		Major

Major Arm Geometry

Arm	Width of carriageway (m)	Has kerbed central reserve	Width of kerbed central reserve (m)	Has right turn bay	Width For Right Turn (m)	Visibility For Right Turn (m)	Blocks?	Blocking Queue (PCU)
C	6.70		0.00		2.20	160.00	✓	0.00

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Minor Arm Geometry

Arm	Minor Arm Type	Lane Width (m)	Lane Width (Left) (m)	Lane Width (Right) (m)	Width at give-way (m)	Width at 5m (m)	Width at 10m (m)	Width at 15m (m)	Width at 20m (m)	Estimate Flare Length	Flare Length (PCU)	Visibility To Left (m)	Visibility To Right (m)
B	One lane	2.75										40	39

Pedestrian Crossings

Arm	Crossing Type
A	None
B	None
C	None

Slope / Intercept / Capacity

Priority Intersection Slopes and Intercepts

Junction	Stream	Intercept (PCU/hr)	Slope for A-B	Slope for A-C	Slope for C-A	Slope for C-B
06	B-A	496.995	0.088	0.222	0.140	0.317
06	B-C	632.257	0.094	0.238	-	-
06	C-B	666.621	0.250	0.250	-	-

The slopes and intercepts shown above do NOT include any corrections or adjustments.

Streams may be combined, in which case capacity will be adjusted.

Values are shown for the first time segment only; they may differ for subsequent time segments.

Traffic Flows

Demand Set Data Options

Default Vehicle Mix	Vehicle Mix Varies Over Time	Vehicle Mix Varies Over Turn	Vehicle Mix Varies Over Entry	Vehicle Mix Source	PCU Factor for a HV (PCU)	Default Turning Proportions	Estimate from entry/exit counts	Turning Proportions Vary Over Time	Turning Proportions Vary Over Turn	Turning Proportions Vary Over Entry
		✓	✓	HV Percentages	2.00				✓	✓

Entry Flows

General Flows Data

Arm	Profile Type	Use Turning Counts	Average Demand Flow (PCU/hr)	Flow Scaling Factor (%)
A	DIRECT	✓	N/A	100.000
B	DIRECT	✓	N/A	100.000
C	DIRECT	✓	N/A	100.000

Turning Proportions

Turning Counts or Proportions (PCU/hr) - Junction 06 (for whole period)

	To			
From		A	B	C
	A	0.000	44.000	487.000
	B	41.000	0.000	45.000
	C	721.000	102.000	0.000

Turning Proportions (PCU) - Junction 06 (for whole period)

	To			
		A	B	C
From	A	0.00	0.08	0.92
	B	0.48	0.00	0.52
	C	0.88	0.12	0.00

Vehicle Mix

Average PCU Per Vehicle - Junction 06 (for whole period)

	To			
		A	B	C
From	A	1.000	1.000	1.000
	B	1.000	1.000	1.000
	C	1.000	1.000	1.000

Heavy Vehicle Percentages - Junction 06 (for whole period)

	To			
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Results

Results Summary for whole modelled period

Stream	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)	Total Queueing Delay (PCU-min)	Average Queueing Delay (s)	Rate Of Queueing Delay (PCU-min/min)	Inclusive Total Queueing Delay (PCU-min)	Inclusive Average Queueing Delay (s)
B-AC	0.25	14.02	0.33	B	86.00	86.00	19.54	13.63	0.33	19.55	13.64
C-AB	0.32	5.11	1.01	A	329.90	329.90	59.85	10.89	1.00	59.88	10.89
C-A	-	-	-	-	493.10	493.10	-	-	-	-	-
A-B	-	-	-	-	44.00	44.00	-	-	-	-	-
A-C	-	-	-	-	487.00	487.00	-	-	-	-	-