


# Ashmore



A single lap, interlocking double plain tile, with the engineered precision and ease of installation of an interlocking tile.

## Colour availability

Key (S) Smooth finish



Old English Dark Red (S)



Smooth Grey (S)



Smooth Brown (S)

| Technical data             |                                                                                                                                                                |                                                               |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------|
| Size of slate              | 267mm x 333mm                                                                                                                                                  |                                                               |
| Minimum pitch*             | 25° (77mm headlap)                                                                                                                                             | 22.5° (92mm headlap)                                          |
| Maximum pitch              | 90°                                                                                                                                                            |                                                               |
| Minimum headlap            | 77mm                                                                                                                                                           |                                                               |
| Maximum gauge              | 190mm                                                                                                                                                          |                                                               |
| Tile thickness             | 16mm (nominal)                                                                                                                                                 |                                                               |
| Cover width                | 302mm (nominal)                                                                                                                                                |                                                               |
| Hanging length             | 235mm (nominal)                                                                                                                                                |                                                               |
| Covering capacity (net)    | 17.5 tiles/m <sup>2</sup> at 77mm headlap                                                                                                                      | 19 tiles/m <sup>2</sup> at 92mm headlap                       |
| Weight of tiling (approx.) | 48kg/m <sup>2</sup> (0.47 kN/m <sup>2</sup> ) at 77mm headlap                                                                                                  | 52kg/m <sup>2</sup> (0.51 kN/m <sup>2</sup> ) at 92mm headlap |
| Battens required (net)     | 5.3 lin.m/m <sup>2</sup> at 77mm headlap                                                                                                                       | 5.8 lin.m/m <sup>2</sup> at 92mm headlap                      |
| Batten size recommended    | 38 x 25mm for rafters/supports not exceeding 450mm centres (fixed to BS 5534)<br>50 x 25mm for rafters/supports not exceeding 600mm centres (fixed to BS 5534) |                                                               |
| Tile nails                 | 45mm x 3.35mm                                                                                                                                                  |                                                               |
| Fixing clips               | Eaves, verge and tile clips                                                                                                                                    |                                                               |
| Authority                  | BS EN 490                                                                                                                                                      |                                                               |

\* The minimum recommended pitch and lap may be influenced by special circumstances, please contact the Technical Advisory Service.

## Sustainability

- ✓ A+ rated in the BRE Green Guide (based on generic rating for UK produced concrete interlocking tiles Element Refs: 812410007, 812410018, 812410049)
- ✓ BES 6001 (Responsible Sourcing) certified
- ✓ Independent carbon footprint certification

## Ashmore fittings

Available in all colours to match main tiles.

Ashmore tiles should be laid broken bond. The required broken bond pattern is created by the introduction of three-quarter width tiles in alternate courses. Tile-and-a-half tiles are available for use at hips and valleys.

