

Junctions 8			
ARCADY 8 - Roundabout Module			
Version: 8.0.2.316 [14 Feb 2013] © Copyright TRL Limited, 2013			
For sales and distribution information, program advice and maintenance, contact TRL: Tel: +44 (0)1344 770758 E-mail: software@trl.co.uk Web: http://www.trlsoftware.co.uk			
The users of this computer program for the solution of an engineering problem are in no way relieved of their responsibility for the correctness of the solution			

Filename: 14. Maurepas Way_London Road Junction.arc8

Path: J:\21834 Woodcroft Farm\004 Transport\Working Documents\Junction Analysis\ARCADY\April 2013 Assessments

Report generation date: 08/07/2013 09:48:24

- » Existing Layout - 2010 Observed, AM
- » Existing Layout - 2010 Observed, PM
- » Existing Layout - 2018 Baseline, AM
- » Existing Layout - 2018 Baseline, PM
- » Existing Layout - 2018 Baseline + Dev, AM
- » Existing Layout - 2018 Baseline + Dev, PM

Summary of junction performance

	AM				PM			
	Queue (PCU)	Delay (s)	RFC	LOS	Queue (PCU)	Delay (s)	RFC	LOS
Existing Layout - 2010 Observed								
Arm A	2.10	6.52	0.68	A	2.60	6.83	0.72	A
Arm B	0.72	2.40	0.42	A	1.19	3.44	0.54	A
Arm C	0.61	2.14	0.38	A	0.29	1.71	0.23	A
Existing Layout - 2018 Baseline								
Arm A	4.27	11.65	0.81	B	5.42	12.62	0.85	B
Arm B	0.94	2.75	0.49	A	1.86	4.67	0.65	A
Arm C	0.84	2.57	0.46	A	0.38	1.93	0.28	A
Existing Layout - 2018 Baseline + Dev								
Arm A	4.39	11.91	0.82	B	5.93	13.66	0.86	B
Arm B	0.97	2.80	0.49	A	1.90	4.76	0.66	A
Arm C	0.86	2.63	0.46	A	0.39	1.94	0.28	A

Values shown are the maximum values over all time segments. Delay is the maximum value of average delay per arriving vehicle.

'D1 - 2010 Observed, AM" model duration: 08:00 - 09:00
 'D2 - 2010 Observed, PM" model duration: 17:00 - 18:00
 'D3 - 2018 Baseline, AM" model duration: 08:00 - 09:00
 'D4 - 2018 Baseline, PM" model duration: 17:00 - 18:00
 'D5 - 2018 Baseline + Dev, AM" model duration: 08:00 - 09:00
 'D6 - 2018 Baseline + Dev, PM" model duration: 17:00 - 18:00
 'D7 - 2023 Baseline, AM" model duration: 08:00 - 09:00
 'D8 - 2023 Baseline, PM" model duration: 17:00 - 18:00
 'D9 - 2023 Baseline + Dev, AM" model duration: 08:00 - 09:00
 'D10 - 2023 Baseline + Dev, PM" model duration: 17:00 - 18:00
 'D11 - 2023 Baseline + Dev (700 Units), AM" model duration: 08:00 - 09:00
 'D12 - 2023 Baseline + Dev (700 Units), PM" model duration: 17:00 - 18:00
 'D13 - 2018 Baseline + Dev (700 Units), AM" model duration: 08:00 - 09:00
 'D14 - 2018 Baseline + Dev (700 Units), PM" model duration: 17:00 - 18:00

Run using Junctions 8.0.2.316 at 08/07/2013 09:48:20

File summary

File Description

Title	Maurepas Way_London Road Junction
Location	Waterlooville
Site Number	14
Date	15/04/2013
Version	
Status	(new file)
Identifier	
Client	
Jobnumber	21834
Enumerator	
Description	

Analysis Options

Vehicle Length (m)	Do Queue Variations	Calculate Residual Capacity	Residual Capacity Criteria Type	RFC Threshold	Average Delay Threshold (s)	Queue Threshold (PCU)
5.75			N/A	0.85	36.00	20.00

Units

Distance Units	Speed Units	Traffic Units Input	Traffic Units Results	Flow Units	Average Delay Units	Total Delay Units	Rate Of Delay Units
m	kph	PCU	PCU	perHour	s	-Min	perMin

Existing Layout - 2010 Observed, AM

Data Errors and Warnings

No errors or warnings

Analysis Set Details

Name	Roundabout Capacity Model	Description	Include In Report	Use Specific Demand Set (s)	Specific Demand Set(s)	Locked	Network Flow Scaling Factor (%)	Network Capacity Scaling Factor (%)	Reason For Scaling Factors
Existing Layout	ARCADY		✓	✓	D1,D2,D3,D4,D5,D6		100.000	100.000	

Demand Set Details

Name	Scenario Name	Time Period Name	Description	Traffic Profile Type	Model Start Time (HH:mm)	Model Finish Time (HH:mm)	Model Time Period Length (min)	Time Segment Length (min)	Results For Central Hour Only	Single Time Segment Only	Locked	Run Automatically	Use Relationship	Rela
2010 Observed, AM	2010 Observed	AM		DIRECT	08:00	09:00	60	15				✓		

Junction Network

Junctions

Name	Junction Type	Arm Order	Grade Separated	Large Roundabout	Do Geometric Delay	Junction Delay (s)	Junction LOS
Hambledon Road_Maurepas Way Junction	Roundabout	A,B,C				3.79	A

File Path: C:\Users\j\Documents\Junctions\21834\21834.j8

Junction Network Options

Driving Side	Lighting
Left	Normal/unknown

Arms

Arms

Arm	Name	Description
A	Hulbert Road	
B	Maurepas Way	
C	London Road	

Capacity Options

Arm	Minimum Capacity (PCU/hr)	Maximum Capacity (PCU/hr)	Assume Flat Start Profile	Initial Queue (PCU)
A	0.00	99999.00		0.00
B	0.00	99999.00		0.00
C	0.00	99999.00		0.00

Roundabout Geometry

Arm	V - Approach road half-width (m)	E - Entry width (m)	I' - Effective flare length (m)	R - Entry radius (m)	D - Inscribed circle diameter (m)	PHI - Conflict (entry) angle (deg)	Exit Only
A	6.60	7.06	2.10	19.90	34.00	17.00	
B	7.64	9.90	6.80	48.30	34.00	15.00	
C	9.99	14.21	7.10	25.00	34.00	15.00	

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Pedestrian Crossings

Arm	Crossing Type
A	None
B	None
C	None

Slope / Intercept / Capacity

Roundabout Slope and Intercept used in model

Arm	Enter slope and intercept directly	Entered slope	Entered intercept (PCU/hr)	Final Slope	Final Intercept (PCU/hr)
A		(calculated)	(calculated)	0.763	2175.138
B		(calculated)	(calculated)	0.914	2860.367
C		(calculated)	(calculated)	1.075	3681.989

The slope and intercept shown above include any corrections and adjustments.

Traffic Flows

Demand Set Data Options

Default Vehicle Mix	Vehicle Mix Varies Over Time	Vehicle Mix Varies Over Turn	Vehicle Mix Varies Over Entry	Vehicle Mix Source	PCU Factor for a HV (PCU)	Default Turning Proportions	Estimate from entry/exit counts	Turning Proportions Vary Over Time	Turning Proportions Vary Over Turn	Turning Proportions Vary Over Entry
		✓	✓	HV Percentages	2.00				✓	✓

Entry Flows

General Flows Data

Arm	Profile Type	Use Turning Counts	Average Demand Flow (PCU/hr)	Flow Scaling Factor (%)
A	DIRECT	✓	N/A	100.000
B	DIRECT	✓	N/A	100.000
C	DIRECT	✓	N/A	100.000

Turning Proportions

Turning Counts or Proportions (PCU/hr) - Junction 14 (for whole period)

		To		
From		A	B	C
	A	48.000	866.000	253.000
	B	790.000	70.000	223.000
	C	499.000	522.000	5.000

Turning Proportions (PCU) - Junction 14 (for whole period)

		To		
From		A	B	C
	A	0.04	0.74	0.22
	B	0.73	0.06	0.21
	C	0.49	0.51	0.00

Vehicle Mix

Average PCU Per Vehicle - Junction 14 (for whole period)

		To		
From		A	B	C
	A	1.000	1.000	1.000
	B	1.000	1.000	1.000
	C	1.000	1.000	1.000

Heavy Vehicle Percentages - Junction 14 (for whole period)

		To		
From		A	B	C
	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Results

Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)	Total Queueing Delay (PCU-min)	Average Queueing Delay (s)	Rate Of Queueing Delay (PCU-min/min)	Inclusive Total Queueing Delay (PCU-min)	Inclusive Average Queueing Delay (s)
A	0.68	6.52	2.10	A	1167.00	1167.00	123.20	6.33	2.05	123.27	6.34
B	0.42	2.40	0.72	A	1083.00	1083.00	43.03	2.38	0.72	43.04	2.38
C	0.38	2.14	0.61	A	1026.00	1026.00	36.38	2.13	0.61	36.38	2.13

Existing Layout - 2010 Observed, PM

Data Errors and Warnings

No errors or warnings

Analysis Set Details

Name	Roundabout Capacity Model	Description	Include In Report	Use Specific Demand Set (s)	Specific Demand Set(s)	Locked	Network Flow Scaling Factor (%)	Network Capacity Scaling Factor (%)	Reason For Scaling Factors
Existing Layout	ARCADY		✓	✓	D1,D2,D3,D4,D5,D6		100.000	100.000	

Demand Set Details

Name	Scenario Name	Time Period Name	Description	Traffic Profile Type	Model Start Time (HH:mm)	Model Finish Time (HH:mm)	Model Time Period Length (min)	Time Segment Length (min)	Results For Central Hour Only	Single Time Segment Only	Locked	Run Automatically	Use Relationship	Rela
2010 Observed, PM	2010 Observed	PM		DIRECT	17:00	18:00	60	15				✓		

Junction Network

Junctions

Name	Junction Type	Arm Order	Grade Separated	Large Roundabout	Do Geometric Delay	Junction Delay (s)	Junction LOS
Hambledon Road_Maurepas Way Junction	Roundabout	A,B,C				4.55	A

Junction Network Options

Driving Side	Lighting
Left	Normal/unknown

Arms

Arms

Arm	Name	Description
A	Hulbert Road	
B	Maurepas Way	
C	London Road	

Capacity Options

Arm	Minimum Capacity (PCU/hr)	Maximum Capacity (PCU/hr)	Assume Flat Start Profile	Initial Queue (PCU)
A	0.00	99999.00		0.00
B	0.00	99999.00		0.00
C	0.00	99999.00		0.00

Roundabout Geometry

Arm	V - Approach road half-width (m)	E - Entry width (m)	I' - Effective flare length (m)	R - Entry radius (m)	D - Inscribed circle diameter (m)	PHI - Conflict (entry) angle (deg)	Exit Only
A	6.60	7.06	2.10	19.90	34.00	17.00	
B	7.64	9.90	6.80	48.30	34.00	15.00	
C	9.99	14.21	7.10	25.00	34.00	15.00	

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Pedestrian Crossings

Arm	Crossing Type
A	None
B	None
C	None

Slope / Intercept / Capacity

Roundabout Slope and Intercept used in model

Arm	Enter slope and intercept directly	Entered slope	Entered intercept (PCU/hr)	Final Slope	Final Intercept (PCU/hr)
A		(calculated)	(calculated)	0.763	2175.138
B		(calculated)	(calculated)	0.914	2860.367
C		(calculated)	(calculated)	1.075	3681.989

The slope and intercept shown above include any corrections and adjustments.

Traffic Flows

Demand Set Data Options

Default Vehicle Mix	Vehicle Mix Varies Over Time	Vehicle Mix Varies Over Turn	Vehicle Mix Varies Over Entry	Vehicle Mix Source	PCU Factor for a HV (PCU)	Default Turning Proportions	Estimate from entry/exit counts	Turning Proportions Vary Over Time	Turning Proportions Vary Over Turn	Turning Proportions Vary Over Entry
		✓	✓	HV Percentages	2.00				✓	✓

Entry Flows

General Flows Data

Arm	Profile Type	Use Turning Counts	Average Demand Flow (PCU/hr)	Flow Scaling Factor (%)
A	DIRECT	✓	N/A	100.000
B	DIRECT	✓	N/A	100.000
C	DIRECT	✓	N/A	100.000

Turning Proportions

Turning Counts or Proportions (PCU/hr) - Junction 14 (for whole period)

		To		
From		A	B	C
	A	78.000	756.000	542.000
	B	770.000	46.000	429.000
	C	305.000	309.000	2.000

Turning Proportions (PCU) - Junction 14 (for whole period)

		To		
From		A	B	C
	A	0.06	0.55	0.39
	B	0.62	0.04	0.34
	C	0.50	0.50	0.00

Vehicle Mix

Average PCU Per Vehicle - Junction 14 (for whole period)

		To		
From		A	B	C
	A	1.000	1.000	1.000
	B	1.000	1.000	1.000
	C	1.000	1.000	1.000

Heavy Vehicle Percentages - Junction 14 (for whole period)

		To		
From		A	B	C
	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Results

Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)	Total Queueing Delay (PCU-min)	Average Queueing Delay (s)	Rate Of Queueing Delay (PCU-min/min)	Inclusive Total Queueing Delay (PCU-min)	Inclusive Average Queueing Delay (s)
A	0.72	6.83	2.60	A	1376.00	1376.00	151.73	6.62	2.53	151.83	6.62
B	0.54	3.44	1.19	A	1245.00	1245.00	70.35	3.39	1.17	70.37	3.39
C	0.23	1.71	0.29	A	616.00	616.00	17.46	1.70	0.29	17.47	1.70

Existing Layout - 2018 Baseline, AM

Data Errors and Warnings

No errors or warnings

Analysis Set Details

Name	Roundabout Capacity Model	Description	Include In Report	Use Specific Demand Set (s)	Specific Demand Set(s)	Locked	Network Flow Scaling Factor (%)	Network Capacity Scaling Factor (%)	Reason For Scaling Factors
Existing Layout	ARCADY		✓	✓	D1,D2,D3,D4,D5,D6		100.000	100.000	

Demand Set Details

Name	Scenario Name	Time Period Name	Description	Traffic Profile Type	Model Start Time (HH:mm)	Model Finish Time (HH:mm)	Model Time Period Length (min)	Time Segment Length (min)	Results For Central Hour Only	Single Time Segment Only	Locked	Run Automatically	Use Relationship	Relative
2018 Baseline, AM	2018 Baseline	AM		DIRECT	08:00	09:00	60	15				✓		

Junction Network

Junctions

Name	Junction Type	Arm Order	Grade Separated	Large Roundabout	Do Geometric Delay	Junction Delay (s)	Junction LOS
Hambledon Road_Maurepas Way Junction	Roundabout	A,B,C				5.87	A

Junction Network Options

Driving Side	Lighting
Left	Normal/unknown

Arms

Arms

Arm	Name	Description
A	Hulbert Road	
B	Maurepas Way	
C	London Road	

Capacity Options

Arm	Minimum Capacity (PCU/hr)	Maximum Capacity (PCU/hr)	Assume Flat Start Profile	Initial Queue (PCU)
A	0.00	99999.00		0.00
B	0.00	99999.00		0.00
C	0.00	99999.00		0.00

Roundabout Geometry

Arm	V - Approach road half-width (m)	E - Entry width (m)	I' - Effective flare length (m)	R - Entry radius (m)	D - Inscribed circle diameter (m)	PHI - Conflict (entry) angle (deg)	Exit Only
A	6.60	7.06	2.10	19.90	34.00	17.00	
B	7.64	9.90	6.80	48.30	34.00	15.00	
C	9.99	14.21	7.10	25.00	34.00	15.00	

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Pedestrian Crossings

Arm	Crossing Type
A	None
B	None
C	None

Slope / Intercept / Capacity

Roundabout Slope and Intercept used in model

Arm	Enter slope and intercept directly	Entered slope	Entered intercept (PCU/hr)	Final Slope	Final Intercept (PCU/hr)
A		(calculated)	(calculated)	0.763	2175.138
B		(calculated)	(calculated)	0.914	2860.367
C		(calculated)	(calculated)	1.075	3681.989

The slope and intercept shown above include any corrections and adjustments.

Traffic Flows

Demand Set Data Options

Default Vehicle Mix	Vehicle Mix Varies Over Time	Vehicle Mix Varies Over Turn	Vehicle Mix Varies Over Entry	Vehicle Mix Source	PCU Factor for a HV (PCU)	Default Turning Proportions	Estimate from entry/exit counts	Turning Proportions Vary Over Time	Turning Proportions Vary Over Turn	Turning Proportions Vary Over Entry
		✓	✓	HV Percentages	2.00				✓	✓

Entry Flows

General Flows Data

Arm	Profile Type	Use Turning Counts	Average Demand Flow (PCU/hr)	Flow Scaling Factor (%)
A	DIRECT	✓	N/A	100.000
B	DIRECT	✓	N/A	100.000
C	DIRECT	✓	N/A	100.000

Turning Proportions

Turning Counts or Proportions (PCU/hr) - Junction 14 (for whole period)

		To		
From		A	B	C
	A	55.000	995.000	290.000
	B	893.000	81.000	258.000
	C	568.000	603.000	6.000

Turning Proportions (PCU) - Junction 14 (for whole period)

		To		
From		A	B	C
	A	0.04	0.74	0.22
	B	0.72	0.07	0.21
	C	0.48	0.51	0.01

Vehicle Mix

Average PCU Per Vehicle - Junction 14 (for whole period)

		To		
From		A	B	C
	A	1.000	1.000	1.000
	B	1.000	1.000	1.000
	C	1.000	1.000	1.000

Heavy Vehicle Percentages - Junction 14 (for whole period)

		To		
From		A	B	C
	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Results

Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)	Total Queueing Delay (PCU-min)	Average Queueing Delay (s)	Rate Of Queueing Delay (PCU-min/min)	Inclusive Total Queueing Delay (PCU-min)	Inclusive Average Queueing Delay (s)
A	0.81	11.65	4.27	B	1340.00	1340.00	243.65	10.91	4.06	243.98	10.92
B	0.49	2.75	0.94	A	1232.00	1232.00	55.93	2.72	0.93	55.94	2.72
C	0.46	2.57	0.84	A	1177.00	1177.00	49.99	2.55	0.83	50.00	2.55

Existing Layout - 2018 Baseline, PM

Data Errors and Warnings

No errors or warnings

Analysis Set Details

Name	Roundabout Capacity Model	Description	Include In Report	Use Specific Demand Set (s)	Specific Demand Set(s)	Locked	Network Flow Scaling Factor (%)	Network Capacity Scaling Factor (%)	Reason For Scaling Factors
Existing Layout	ARCADY		✓	✓	D1,D2,D3,D4,D5,D6		100.000	100.000	

Demand Set Details

Name	Scenario Name	Time Period Name	Description	Traffic Profile Type	Model Start Time (HH:mm)	Model Finish Time (HH:mm)	Model Time Period Length (min)	Time Segment Length (min)	Results For Central Hour Only	Single Time Segment Only	Locked	Run Automatically	Use Relationship	Relative
2018 Baseline, PM	2018 Baseline	PM		DIRECT	17:00	18:00	60	15				✓		

Junction Network

Junctions

Name	Junction Type	Arm Order	Grade Separated	Large Roundabout	Do Geometric Delay	Junction Delay (s)	Junction LOS
Hambledon Road_Maurepas Way Junction	Roundabout	A,B,C				7.51	A

Junction Network Options

Driving Side	Lighting
Left	Normal/unknown

Arms

Arms

Arm	Name	Description
A	Hulbert Road	
B	Maurepas Way	
C	London Road	

Capacity Options

Arm	Minimum Capacity (PCU/hr)	Maximum Capacity (PCU/hr)	Assume Flat Start Profile	Initial Queue (PCU)
A	0.00	99999.00		0.00
B	0.00	99999.00		0.00
C	0.00	99999.00		0.00

Roundabout Geometry

Arm	V - Approach road half-width (m)	E - Entry width (m)	I' - Effective flare length (m)	R - Entry radius (m)	D - Inscribed circle diameter (m)	PHI - Conflict (entry) angle (deg)	Exit Only
A	6.60	7.06	2.10	19.90	34.00	17.00	
B	7.64	9.90	6.80	48.30	34.00	15.00	
C	9.99	14.21	7.10	25.00	34.00	15.00	

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Pedestrian Crossings

Arm	Crossing Type
A	None
B	None
C	None

Slope / Intercept / Capacity

Roundabout Slope and Intercept used in model

Arm	Enter slope and intercept directly	Entered slope	Entered intercept (PCU/hr)	Final Slope	Final Intercept (PCU/hr)
A		(calculated)	(calculated)	0.763	2175.138
B		(calculated)	(calculated)	0.914	2860.367
C		(calculated)	(calculated)	1.075	3681.989

The slope and intercept shown above include any corrections and adjustments.

Traffic Flows

Demand Set Data Options

Default Vehicle Mix	Vehicle Mix Varies Over Time	Vehicle Mix Varies Over Turn	Vehicle Mix Varies Over Entry	Vehicle Mix Source	PCU Factor for a HV (PCU)	Default Turning Proportions	Estimate from entry/exit counts	Turning Proportions Vary Over Time	Turning Proportions Vary Over Turn	Turning Proportions Vary Over Entry
		✓	✓	HV Percentages	2.00				✓	✓

Entry Flows

General Flows Data

Arm	Profile Type	Use Turning Counts	Average Demand Flow (PCU/hr)	Flow Scaling Factor (%)
A	DIRECT	✓	N/A	100.000
B	DIRECT	✓	N/A	100.000
C	DIRECT	✓	N/A	100.000

Turning Proportions

Turning Counts or Proportions (PCU/hr) - Junction 14 (for whole period)

		To		
From		A	B	C
	A	91.000	862.000	622.000
	B	886.000	53.000	498.000
	C	351.000	359.000	2.000

Turning Proportions (PCU) - Junction 14 (for whole period)

		To		
From		A	B	C
	A	0.06	0.55	0.39
	B	0.62	0.04	0.35
	C	0.49	0.50	0.00

Vehicle Mix

Average PCU Per Vehicle - Junction 14 (for whole period)

		To		
From		A	B	C
	A	1.000	1.000	1.000
	B	1.000	1.000	1.000
	C	1.000	1.000	1.000

Heavy Vehicle Percentages - Junction 14 (for whole period)

		To		
From		A	B	C
	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Results

Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)	Total Queueing Delay (PCU-min)	Average Queueing Delay (s)	Rate Of Queueing Delay (PCU-min/min)	Inclusive Total Queueing Delay (PCU-min)	Inclusive Average Queueing Delay (s)
A	0.85	12.62	5.42	B	1575.00	1575.00	306.38	11.67	5.11	306.85	11.69
B	0.65	4.67	1.86	A	1437.00	1437.00	109.29	4.56	1.82	109.34	4.57
C	0.28	1.93	0.38	A	712.00	712.00	22.78	1.92	0.38	22.78	1.92

Existing Layout - 2018 Baseline + Dev, AM

Data Errors and Warnings

No errors or warnings

Analysis Set Details

Name	Roundabout Capacity Model	Description	Include In Report	Use Specific Demand Set (s)	Specific Demand Set(s)	Locked	Network Flow Scaling Factor (%)	Network Capacity Scaling Factor (%)	Reason For Scaling Factors
Existing Layout	ARCADY		✓	✓	D1,D2,D3,D4,D5,D6		100.000	100.000	

Demand Set Details

Name	Scenario Name	Time Period Name	Description	Traffic Profile Type	Model Start Time (HH:mm)	Model Finish Time (HH:mm)	Model Time Period Length (min)	Time Segment Length (min)	Results For Central Hour Only	Single Time Segment Only	Locked	Run Automatically	Use Relationship	Relatio
2018 Baseline + Dev, AM	2018 Baseline + Dev	AM		DIRECT	08:00	09:00	60	15				✓		

Junction Network

Junctions

Name	Junction Type	Arm Order	Grade Separated	Large Roundabout	Do Geometric Delay	Junction Delay (s)	Junction LOS
Hambledon Road_Maurepas Way Junction	Roundabout	A,B,C				5.99	A

Junction Network Options

Driving Side	Lighting
Left	Normal/unknown

Arms

Arms

Arm	Name	Description
A	Hulbert Road	
B	Maurepas Way	
C	London Road	

Capacity Options

Arm	Minimum Capacity (PCU/hr)	Maximum Capacity (PCU/hr)	Assume Flat Start Profile	Initial Queue (PCU)
A	0.00	99999.00		0.00
B	0.00	99999.00		0.00
C	0.00	99999.00		0.00

Roundabout Geometry

Arm	V - Approach road half-width (m)	E - Entry width (m)	I' - Effective flare length (m)	R - Entry radius (m)	D - Inscribed circle diameter (m)	PHI - Conflict (entry) angle (deg)	Exit Only
A	6.60	7.06	2.10	19.90	34.00	17.00	
B	7.64	9.90	6.80	48.30	34.00	15.00	
C	9.99	14.21	7.10	25.00	34.00	15.00	

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Pedestrian Crossings

Arm	Crossing Type
A	None
B	None
C	None

Slope / Intercept / Capacity

Roundabout Slope and Intercept used in model

Arm	Enter slope and intercept directly	Entered slope	Entered intercept (PCU/hr)	Final Slope	Final Intercept (PCU/hr)
A		(calculated)	(calculated)	0.763	2175.138
B		(calculated)	(calculated)	0.914	2860.367
C		(calculated)	(calculated)	1.075	3681.989

The slope and intercept shown above include any corrections and adjustments.

Traffic Flows

Demand Set Data Options

Default Vehicle Mix	Vehicle Mix Varies Over Time	Vehicle Mix Varies Over Turn	Vehicle Mix Varies Over Entry	Vehicle Mix Source	PCU Factor for a HV (PCU)	Default Turning Proportions	Estimate from entry/exit counts	Turning Proportions Vary Over Time	Turning Proportions Vary Over Turn	Turning Proportions Vary Over Entry
		✓	✓	HV Percentages	2.00				✓	✓

Entry Flows

General Flows Data

Arm	Profile Type	Use Turning Counts	Average Demand Flow (PCU/hr)	Flow Scaling Factor (%)
A	DIRECT	✓	N/A	100.000
B	DIRECT	✓	N/A	100.000
C	DIRECT	✓	N/A	100.000

Turning Proportions

Turning Counts or Proportions (PCU/hr) - Junction 14 (for whole period)

		To		
		A	B	C
From	A	55.000	1000.000	292.000
	B	913.000	81.000	258.000
	C	576.000	603.000	6.000

Turning Proportions (PCU) - Junction 14 (for whole period)

		To		
		A	B	C
From	A	0.04	0.74	0.22
	B	0.73	0.06	0.21
	C	0.49	0.51	0.01

Vehicle Mix

Average PCU Per Vehicle - Junction 14 (for whole period)

		To		
		A	B	C
From	A	1.000	1.000	1.000
	B	1.000	1.000	1.000
	C	1.000	1.000	1.000

Heavy Vehicle Percentages - Junction 14 (for whole period)

		To		
		A	B	C
From	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Results

Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)	Total Queueing Delay (PCU-min)	Average Queueing Delay (s)	Rate Of Queueing Delay (PCU-min/min)	Inclusive Total Queueing Delay (PCU-min)	Inclusive Average Queueing Delay (s)
A	0.82	11.91	4.39	B	1347.00	1347.00	250.02	11.14	4.17	250.37	11.15
B	0.49	2.80	0.97	A	1252.00	1252.00	57.79	2.77	0.96	57.80	2.77
C	0.46	2.63	0.86	A	1185.00	1185.00	51.40	2.60	0.86	51.41	2.60

Existing Layout - 2018 Baseline + Dev, PM

Data Errors and Warnings

No errors or warnings

Analysis Set Details

Name	Roundabout Capacity Model	Description	Include In Report	Use Specific Demand Set (s)	Specific Demand Set(s)	Locked	Network Flow Scaling Factor (%)	Network Capacity Scaling Factor (%)	Reason For Scaling Factors
Existing Layout	ARCADY		✓	✓	D1,D2,D3,D4,D5,D6		100.000	100.000	

Demand Set Details

Name	Scenario Name	Time Period Name	Description	Traffic Profile Type	Model Start Time (HH:mm)	Model Finish Time (HH:mm)	Model Time Period Length (min)	Time Segment Length (min)	Results For Central Hour Only	Single Time Segment Only	Locked	Run Automatically	Use Relationship	Relatio
2018 Baseline + Dev, PM	2018 Baseline + Dev	PM		DIRECT	17:00	18:00	60	15				✓		

Junction Network

Junctions

Name	Junction Type	Arm Order	Grade Separated	Large Roundabout	Do Geometric Delay	Junction Delay (s)	Junction LOS
Hambledon Road_Maurepas Way Junction	Roundabout	A,B,C				8.01	A

Junction Network Options

Driving Side	Lighting
Left	Normal/unknown

Arms

Arms

Arm	Name	Description
A	Hulbert Road	
B	Maurepas Way	
C	London Road	

Capacity Options

Arm	Minimum Capacity (PCU/hr)	Maximum Capacity (PCU/hr)	Assume Flat Start Profile	Initial Queue (PCU)
A	0.00	99999.00		0.00
B	0.00	99999.00		0.00
C	0.00	99999.00		0.00

Roundabout Geometry

Arm	V - Approach road half-width (m)	E - Entry width (m)	I' - Effective flare length (m)	R - Entry radius (m)	D - Inscribed circle diameter (m)	PHI - Conflict (entry) angle (deg)	Exit Only
A	6.60	7.06	2.10	19.90	34.00	17.00	
B	7.64	9.90	6.80	48.30	34.00	15.00	
C	9.99	14.21	7.10	25.00	34.00	15.00	

Geometries for Arm C are measured opposite Arm B. Geometries for Arm A (if relevant) are measured opposite Arm D.

Pedestrian Crossings

Arm	Crossing Type
A	None
B	None
C	None

Slope / Intercept / Capacity

Roundabout Slope and Intercept used in model

Arm	Enter slope and intercept directly	Entered slope	Entered intercept (PCU/hr)	Final Slope	Final Intercept (PCU/hr)
A		(calculated)	(calculated)	0.763	2175.138
B		(calculated)	(calculated)	0.914	2860.367
C		(calculated)	(calculated)	1.075	3681.989

The slope and intercept shown above include any corrections and adjustments.

Traffic Flows

Demand Set Data Options

Default Vehicle Mix	Vehicle Mix Varies Over Time	Vehicle Mix Varies Over Turn	Vehicle Mix Varies Over Entry	Vehicle Mix Source	PCU Factor for a HV (PCU)	Default Turning Proportions	Estimate from entry/exit counts	Turning Proportions Vary Over Time	Turning Proportions Vary Over Turn	Turning Proportions Vary Over Entry
		✓	✓	HV Percentages	2.00				✓	✓

Entry Flows

General Flows Data

Arm	Profile Type	Use Turning Counts	Average Demand Flow (PCU/hr)	Flow Scaling Factor (%)
A	DIRECT	✓	N/A	100.000
B	DIRECT	✓	N/A	100.000
C	DIRECT	✓	N/A	100.000

Turning Proportions

Turning Counts or Proportions (PCU/hr) - Junction 14 (for whole period)

		To		
From		A	B	C
	A	91.000	877.000	629.000
	B	894.000	53.000	498.000
	C	354.000	359.000	2.000

Turning Proportions (PCU) - Junction 14 (for whole period)

		To		
From		A	B	C
	A	0.06	0.55	0.39
	B	0.62	0.04	0.34
	C	0.50	0.50	0.00

Vehicle Mix

Average PCU Per Vehicle - Junction 14 (for whole period)

		To		
From		A	B	C
	A	1.000	1.000	1.000
	B	1.000	1.000	1.000
	C	1.000	1.000	1.000

Heavy Vehicle Percentages - Junction 14 (for whole period)

		To		
From		A	B	C
	A	0.000	0.000	0.000
	B	0.000	0.000	0.000
	C	0.000	0.000	0.000

Results

Results Summary for whole modelled period

Arm	Max RFC	Max Delay (s)	Max Queue (PCU)	Max LOS	Average Demand (PCU/hr)	Total Junction Arrivals (PCU)	Total Queueing Delay (PCU-min)	Average Queueing Delay (s)	Rate Of Queueing Delay (PCU-min/min)	Inclusive Total Queueing Delay (PCU-min)	Inclusive Average Queueing Delay (s)
A	0.86	13.66	5.93	B	1597.00	1597.00	333.30	12.52	5.56	333.87	12.54
B	0.66	4.76	1.90	A	1445.00	1445.00	111.88	4.65	1.86	111.93	4.65
C	0.28	1.94	0.39	A	715.00	715.00	23.02	1.93	0.38	23.02	1.93