

PERMIT

carbonate
it remain
the same

125x50mm LAPPED
DOES AT 400mm
FLUNG 250mm
L TIO AT 1:3mbs

in all round WITH
KIL PROVIDES NO
1000 6mm KIL GAP

USE LIGN TO ROOF TO WC USE SPEC
NO BEFIDE BUT USE 125x50mm LAPPED
AND CEILING JOINT AND TILE COLOUR
TO MATCH EXISTING BUT CAPABLE
OF BEING LAID AT LOW PITCH STAIN.
USE STUP BACK ROOF ON EXISTING, THAT
ROOF EXTN BUILD UP TO FORM GABLE END
NO max SPEC AND INSET CAVITY
TRAIN NO REQUIRED

TO MATCH
+ 50mm
section d
using bond
removed
train AND
DEVELO GATED

NEW BATHROOM
WINDOW CATHIC
LIMIT OVER

5
CAVITY TRAIN AND
LEAD FLASHING

USE ANY AIRBLOCK
BLOCKED TO BE
DUSTED TO EXTN AIR

ROOF DPC

100mm

WC

consrvty

section bb

DEEP TO LEVEL
TO ROAD TO EXTN
ADDITIONS NOTE
CLASS "A" CONC
BELOW GROUND LEVEL

floor

min 100mm CONC on min 100mm HARDWARE
1200 GAUGE POLYETHYLENE DPM 50mm
POLY STYRENE INSULATION AND 75mm
SAND/CEMENT SURFED WITH ANT-CRACK
MESH

HAVANT BOROUGH COUNCIL
DEVELOPMENT CONTROL

23 MAR 2011

RECEIVED