NOTES

1. All works to be in accordance with the WRc guide "Sewers for Adoption – 6th Edition" and specific requirements of Southern Water.
2. 150mm diameter pipework to be extra strength vitrified clay to BS EN 295 on class S bed & surround.
3. 225mm diameter pipework to be extra strength vitrified clay to BS EN 295 or concrete class M to BS 5911 on class S bed & surround.
4. 300mm diameter and greater pipework to be concrete class M to BS 5911 on class B bed & haunch.
5. Where cover to pipes is less than 1.2m concrete bed and surround should be used.

Manhole Number	Cover Level	Connections	Pipe				Manhole Size	Types	
Coordinates	Depth To Soffit		Code	Inverts	Diams Inv-soff			Manhole	Cover
F1	51.337	1	1	1.008	49.694	150	-	PUMPING STATION	D400
E. 468344.256	1.493	0							
N. 107833.735									
F2	51.702	1 0	1	1.007	49.795	150	1200	TYPE B	D400
E. 468339.584	1.757		0	1.008	49.795	150			
N. 107820.106									
F3	51.852	2 1 0	1	3.000	49.886	150	1200	TYPE B	D400
E. 468351.939	1.816		2	1.006	49.886	150			
N. 107816.597			0	1.007	49.886	150			
F4	51.735	1 0	1	1.005	50.072	150	1200	TYPE B	D400
E. 468377.642	1.513		0	1.006	50.072	150			
N. 107824.974									
F5	52.022	1 0	1	1.003	50.335	150	1200	TYPE B	D400
E. 468416.887	1.537		0	1.004	50.335	150			
N. 107827.554									
F6	52.267	2 1 0	1	1.002	50.500	150	1200	TYPE B	D400
E. 468440.320	1.617		2	2.002	50.500	150			
N. 107.835.800			0	1.003	50.500	150			

Manhole Number	Cover Level	Connections	Pipe				Manhole Size	Types	
Coordinates	Depth To Soffit		Code	Inverts	Diams Inv-soff			Manhole	Cover
F7	52.948	1 0	1	1.001	50.867	150	1200	TYPE B	D400
E. 468459.987	1.931		0	1.002	50.867	150			
N. 107784.294									
F8	53.101	1 0	1	1.000	51.511	100	1200	TYPE B	D400
E. 468468.225	1.440		0	1.001	51.461	150			
N. 107774.579									
F9	53.448	0	1	1.000	52.050	100	1240 x 675	TYPE C	D400
E. 468508.933	1.248								
N. 107788.777									
F10	52.605	1 0	1	2.001	51.339	100	1240 x 675	TYPE C	D400
E. 468469.884	1.116		0	2.002	51.289	150			
N. 107845.444									
F11	53.366	0					1240 x 675	TYPE C	D400
E. 468527.963	1.150								
N. 107841.939			0	2.000	52.066	100			
F12	52.695	1	1	1.002	50.752	150	-	EXISTING	-
E. 468298.981	1.793								
N. 107742.182									

Manhole Number	Cover Level	Connections	Pipe				Manhole Size	Types	
Coordinates	Depth To Soffit		Code	Inverts	Diams Inv-soff			Manhole	Cover
F13	52.716	1 0	1	1.001	50.974	150	1200	TYPE B	D400
E. 468300.370	1.592		0	1.002	50.974	150			
N. 107744.896									
F14	53.612	1 0	1	1.000	51.570	150	1200	TYPE B	D400
E. 468347.824	1.892		0	1.001	51.570	150			
N. 107740.822									
F15	53.367	0	1	1.000	51.782	150	1240 x 675	TYPE C	D400
E. 468349.183	1.455								
N. 107756.151									

HAVANT BOROUGH COUNCIL
28 FEB 2013
RECEIVED

Rev.	Date	Details	By	Chkd
		MH numbers adjusted to suit		
A	27.07.12	Original MHs 5 , 12 and 14 removed .	IDC	KMR
B	08.08.12	Pn 1.000 and 2.000 revised to 100mmDia Pipe	SRV	IDC
C	03.09.12	Revised in accordance with Pimps detailed design	SRV	IDC
D	25.09.12	F15 Cover level revised	SRV	IDC

Client:- DAVID WILSON HOMES

Site:- Stakes Road, Purbrook, Hampshire

Drawing Title:- FOUL SEWER SETTING OUT SCHEDULES

Date: Mar.2012 | Scales: NTS

Drawn: IDC | Checked: KMR

Drawing No. BSC/E3945/106 D

Rogers Cory Partnership
Civil, Structural and Architectural Consultants
the old school old school road
hook hampshire rg27 9nj
t 01256 769269 e mail@rcpconsultants.co.uk
f 01256 763048 w rcpconsultants.co.uk