

## Notes

1 - Roof to be Glass

2 - Windows double glazed with low emissivity glazing.  
All in accord with BR App Doc Part N. Trickle vents  
in compliance with App Doc BR Part F (+ Ammendments)  
8,000mm<sup>2</sup> to habitable rooms, 4,000mm<sup>2</sup> to kitchen,  
bath & WC.

All areas under 800mm from FFL, all door glazing, all  
areas below 1500mm from FFL and within 300mm of  
doors to be glazed with safety glass.

3 - Roof - Aluminium & PVCu

4 - Roof & Window Frames - Woodgrain finish

5 - Footings - Size of footings in accord with  
Approved Documents and to LA approval.

6 - Floor - Insulated solid floor with screed finish.

7 - Any existing air-bricks ducted through new floor.

8 - All internal conservatory walls to be  
plaster finish.

9 - Approximate int.volume of conservatory - 56.9 cu.m.

10 - Approximate floor area of conservatory - 20.2 sq. m.

11 - Brickwork - Cavity wall constructed with 50mm  
cavity, filled with min 25 mm insulation. Blockwork to be with  
Thermalite blocks or similar and approved. External  
faces to be in Faced brick to match existing brickwork.

### Site:

Mr J Thame  
29 Cornbrook Grove  
Waterlooville  
PO7 8RD

### Details

Notes

Job No.  
07/385

Drwg No.  
385/12

Reference  
Thame HBC

Scale  
N/A

Date  
July 2013