

PERMIT

all windows and doors to satisfy requirements of approved document 'L' revised 01/04/02, and fitted 'FENSA' registered contractor.

New windows or glazed doors to achieve a max value of $< 0.2W/m^2K$ using 'Low E' glass $7W/m^2K$ overall - $1.1W/m^2K$ centre pane
All new frames to have trickle vents to give unobstructed permanent ventilation

All glazing in critical areas to be toughened safety glass to conform with approved document N1

Drainage:-

All pipework and connections to be in strict accordance with approved doc H

Waste pipes and traps are to be in UPVC to BS5255 & BS 3943, as follows:

150mm from a basin, 40mm from a sink

150mm deep bottle trap from basin and sink

Wastes exceeding 3000mm long are to be fitted with an anti-vac valve

,

Section A-A (1:50)

Serial Number: 01977900

Supplied by: www.ukmapcentre.com

Centre coordinates of this map: 470

Produced 29 Nov 2010 from the Ordnance Survey

Geographic Database and incorporating the latest

revision available at this date.

© Crown Copyright 2010.



WildCry Techn
1 Bealing Clo
Southampton
SO16 3AW
email: admin@

SCHEME TITLE

16 Priorsde
Havant PO

DRAWING TITLE

Conversion
to 2x1 bed Fla

CREATED MAH	DATE Nov 2010	CHECKED
----------------	------------------	---------

DRAWING NUMBER Prior001	PROJECT REVISION
-----------------------------------	---------------------

26 JAN 2011

RECEIVED

© Copyright - WildCry Technical Services 2010