

APP/10/0070



Bexhill Red 4010



Capital Multi Stock 0717

Thakeham Red Multi Stock 0709 | Private House, West Sussex



15

Red/Red Multi Stocks



Hamsey Mixed Stock 4517

Need a brick for corners
and virtually
any angle?



See the easyangle® in our Everyday Range
page 71-73. Ideal for conservatories.



Standard brick height is 65mm, where you see this
icon with 50mm, 68mm, 73mm or 80mm then the
bricks are also available in this height.

Chimneys Brickwork Components pages 80-81

Cissbury Red Multi Stock 0767
Private House, Buckinghamshire



16

Red/Red Multi Stocks



Chailey Stock 4501



Standard brick height is 65mm, where you see this icon with 50mm, 68mm, 73mm or 80mm then the bricks are also available in this height.



West Hoathly Wakehurst Multi Stock 0738



Artbury Red Multi Stock 3019



West Hoathly Medium Multi Stock 0731



Petworth Multi Stock 0700



Chailey Rustic Stock 4514



Mayfield Multi Stock 4003



Barcombe Kilnwood Multi Stock 4525

Dentil detailing is made easy with our Brickwork Components, pages 78-79

APP/10/0070

Ludlow Major

Simple, strong lines exploit the interplay between light and shade.



Colour availability



Greystone (G)



Smooth Grey (S)



Smooth Brown (S)



Antique Brown (G)



Dark Red (G)



Old English Dark Red (S)



Mosborough Red (S)

Key (G) Granular finish
(S) Smooth finish

* Second Hand Tile

Technical data

Size of tile	420mm x 330mm
Minimum pitch*	25° Smooth (75mm headlap) 30° Granular (75mm headlap) 22.5° Smooth (100mm headlap)
Maximum pitch	90°
Minimum headlap	75mm
Maximum gauge	345mm
Profile depth	20mm $\geq d \geq$ 5mm
Cover width	295mm (nominal)
Hanging length	399mm (nominal)
Covering capacity (net)	9.6 tiles/m ² at 75mm headlap 10.6 tiles/m ² at 100mm headlap
Weight of tiling (approx.)	45 kg/m ² (0.44 kN/m ²) at 75mm headlap 49 kg/m ² (0.48 kN/m ²) at 100mm headlap
Battens required (net)	2.9 lin.m/m ² at 75mm headlap 3.1 lin.m/m ² at 100mm headlap
Batten size recommended	38 x 25mm for rafters/supports not exceeding 450mm centres (fixed to BS 5534) 50 x 25mm for rafters/supports not exceeding 600mm centres
Tile nails	55mm x 3.35mm
Fixing clips	Eaves, verge and tile clips
Authority	BS EN 490

* The minimum recommended pitch and lap may be influenced by special circumstances, please contact the Technical Advisory Service.



BS EN 490