PERMEABLE PAVING LEGEND

- CONCRETE BAFFLE WITHIN PERMEABLE SUBBASE
- SERVICE CORRIDOR. BLOCK PAVING LOCATED ABOVE UTILITY CORRIDOR TO BE LINED.

PERMEABLE PAVING CONSTRUCTION (ALL LAYERS) DEPTH RANGE DATA

CATCHMENT NUMBER	MIN. DEPTH (m)*	COLOUR	PLAN AREA (m^2)**	DEPTH FROM SUBBASE FORMATION TO GROUNDWATER (m)
1	1.050		336	>1.000
2	1.275		522	>1.000
3	1.000		1270	>1.000
4	1.400		531	<1.000***
5	0.850		896	<1.000***
6	1.250		527	>1.000
7	1.000		883	>1.000
8	0.600		386	>1.000
9	0.650		736	>1.000
10	1.625		329	>1.000
11	1.050		559	>1.000
12	0.600		705	>1.000

* SUBBASE SLOPE ASSUMED TO BE FLAT. CONCRETE BAFFLES WITHIN PERMEABLE SUBBASE TO BE INTRODUCED AT INTERVALS TO LIMIT DEPTH OF SUBBASE IF REQUIRED.
** AREA OF PAVING ABOVE 2m MIN. SERVICE CORRIDOR EXCLUDED.
*** GROUNDWATER LEVELS IN VICINITY OF CACTHMENT ASSUMED TO BE PERCHED AND NOT REPRESENTATIVE OF TRUE GROUNDWATER LEVELS.

NOTES

© This drawing is the copyright of ARCH Associates Limited. It may not be copied, altered or reproduced without their written authority. This drawing must not be scaled. IF IN DOUBT ASK.

GENERAL NOTES

1. THIS DRAWING IS TO BE READ IN CONJUNCTION WITH ALL RELEVANT ARCHITECTS, ENGINEERS AND SPECIALISTS DRAWINGS AND DETAILS.
2. ALL FIGURED DIMENSIONS TO BE TAKEN IN PREFERENCE TO SCALED DIMENSIONS.
3. ANY DISCREPANCIES BETWEEN THIS DRAWING AND OTHER INFORMATION IS TO BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO THE COMMENCEMENT OF THE WORKS ON SITE.
4. THE MAIN CONTRACTOR SHALL BE RESPONSIBLE FOR THE SETTING OUT AND ACCURACY OF ALL DIMENSIONS.
5. THE CONTRACTOR IS TO ENSURE THE STABILITY AND STRUCTURAL INTEGRITY OF THE EXISTING PROPERTY AT ALL TIMES DURING WORKS AND IS TO BE RESPONSIBLE FOR ALL PROPPING AND SHORING AS REQUIRED.
6. MAIN CONTRACTOR TO PROVIDE AND FIX SUITABLE BRACING AND PROPPING FOR ALL ELEMENTS IN THE TEMPORARY CONDITION DURING CONSTRUCTION STAGE, SUCH AS TO ENSURE STRUCTURE STABILITY AT ALL TIMES.
7. IT IS THE CONTRACTORS SOLE RESPONSIBILITY FOR ASCERTAINING SAFE DISPOSAL OF ANY OFF-SITE EXCAVATED SPOIL. NO CLAIM RESULTING FROM ABNORMAL TIP REQUIREMENTS WILL BE ENTERTAINED.

DRAINAGE NOTES

1. REFER TO DRAWING FHL022-AAL-ED-XX-LS-C-5199 FOR COMPRENHENSIVE DRAINAGE NOTES.

KEY TO HEALTH AND SAFETY SYMBOLS

THESE NOTES ARE BASED ON THE USE OF EXPERIENCED AND COMPETENT CONTRACTORS CARRYING OUT THE WORK USING AN APPROVED SAFE METHOD OF WORKING

- INDICATES A RESIDUAL RISK REQUIRING A COMPULSORY ACTION
- INDICATES A RESIDUAL RISK REQUIRING A PROHIBITIVE ACTION
- INDICATES A RESIDUAL RISK AS A WARNING
- INDICATES A RESIDUAL RISK FOR INFORMATION

COLOURED DRAWING
REQUEST A COLOURED COPY IF THIS STAMP IS NOT RED

Rev.	Date	Description	By
P01	30.01.2026	PRELIMINARY ISSUE FOR COMMENT	TA

ARCH ASSOCIATES
01489 890004
admin@archassociates.co.uk
www.archassociates.co.uk

Client
FOREMAN HOMES

Architect
HGP ARCHITECTS

Project title
GOODWILLIES TIMBER YARD, PURBROOK.

Drawing title
DRAINAGE, PERMEABLE PAVING.

Scale	Paper size	Date	Drawn by	Checked by	Status
1:750	A1	JAN 2026	TA	CH	S3

Name
Project code | Originator | Functional breakdown | Spatial breakdown | Form | Discipline | Number | Revision
FHL022- AAL - ED - XX - DP - C - 5105 - P01